

## Module plate 1-hole 4p, size 4

Part no. **NZM4-4-XKM1**  
**266815**

<b>General specifications</b>		
Product name		Eaton Moeller series NZM connection type
Part no.		NZM4-4-XKM1
EAN		4015082668150
Product Length/Depth		61 millimetre
Product height		10 millimetre
Product width		180 millimetre
Product weight		0.825 kilogram
Compliances		IEC RoHS conform
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Connection type
<b>Delivery program</b>		
Type		Accessory Module plate Terminal
Number of poles		Four-pole
Amperage Rating		≤ 1250 A
Special features		One hole
Frame		NZM4
Suitable for		Copper cable lugs Four-pole
Used with		NZM4-4, N4-4
<b>Technical Data - Mechanical</b>		
Special features		One hole
<b>Technical Data - Mechanical - Terminals</b>		
Terminal capacity (flexible cable)		120 mm <sup>2</sup> - 300 mm <sup>2</sup> (1x) Max. 600 AWG/kcmil (2x) 250 - 600 AWG/kcmil (1x) 95 mm <sup>2</sup> - 300 mm <sup>2</sup> (2x)
Terminal capacity (copper busbar)		40 mm x 10 mm (2x) 50 mm x 10 mm (2x)
Terminal capacity (copper strip)		10 segments of 40 mm x 1 mm (2x) 10 segments of 50 mm x 1 mm (2x)
<b>Design verification as per IEC/EN 61439</b>		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.

10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ecI@ss13-27-37-13-05 [ACN990017])			
Suitable for number of poles			4