## **DATASHEET - NZM3-XCI48-TVDVR**



## Insulated enclosure, box size HxWxD=750x375x275mm, for NZM size 4

Powering Business Worldwide\*

Part no. NZM3-XCI48-TVDVR Catalog No. 271530

### **Delivery program**

belivery program			
Product range			xEnergy Safety Ci
Accessories			Prepared enclosures
Description			With door coupling rotary handle Complete with all required functional parts
Function			Red-yellow for emergency switching off
Locking facility			Lockable in the 0 position using up to 3 padlocks on the handle and/or switch each. Additionally with cover interlock.
Accessories			Accessories, others
Number of poles			3/4 pole
Standard/Approval			IEC
Construction size			NZM3
Degree of Protection			IP65
Rated uninterrupted current $I_{\text{u}}$ at max. cross-section	I <sub>u</sub>	Α	≦ 400 A
Basic enclosure			C148-250
Terminal for retrofitting of 5th conductor (neutral conductor)			K95/1N/BR, K150/1/BR, K240/1/BR, K2X240/1/BR
For use with			NZM3(-4), PN3(-4), N(S)3(-4)

#### Notes

Suitable for installation of circuit-breakers and switch-disconnectors Enclosure for separate mounting with top and bottom cable entry.

Include fixing straps for wall mounting.

Cannot be used in combination with NZM...-XR... remote operator...,

 $\ensuremath{\mathsf{NZM}} \dots \text{-} \ensuremath{\mathsf{XSV}}$  plug-in unit or  $\ensuremath{\mathsf{NZM}} \dots \text{-} \ensuremath{\mathsf{XAV}}$  with drawable unit.

Insulated additional terminal for 4th or 5th pole should be ordered separately.

CI-K5 enclosure with hard metric knock-outs

CI23 enclosure with flanges

CI43, CI45 and CI48 feature gland plates.

Only for switches with box terminal for direct connection of cables.

## **Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss10.0.1-27-37-13-01 [AKN343014])

	Plastic
mm	375
mm	750
mm	275
	Yes
	Yes
	Surface mounting
	IP65
	Other
	mm mm

# Dimensions

