

## Miniature circuit breaker (MCB), 2 A, 1p, characteristic: B

**Part no.** FAZ-B2/1  
**278523**  
**EL Number** 1691003  
**(Norway)**

General specifications	
Product name	Eaton Moeller series xEffect - FAZ MCB
Part no.	FAZ-B2/1
EAN	4015082785239
Product Length/Depth	80 millimetre
Product height	75.5 millimetre
Product width	17.7 millimetre
Product weight	0.113 kilogram
Compliances	UL CSA09 (with supplementary protector only) RoHS conform
Certifications	UL (File No. E177451) IEC/EN 60947-2 North America (UL recognized, CSA certified) CSA (File No. 204453) UL 1077 CSA-C22.2 No. 235 CSA (Class No. 3215-30) UL (Category Control Number QVNU2, QVNU8) IEC/EN 60898 CE marking IEC 61373 EN45545-2
Product Tradename	xEffect - FAZ
Product Type	MCB
Product Sub Type	None
Catalog Notes	For applications that require protection due to potential wiring damage at low fault conditions.
Delivery program	
Application	Branch circuits, not as BCPD Switchgear for industrial and advanced commercial applications xEffect - Switchgear for industrial and advanced commercial applications
Number of poles	Single-pole
Number of poles (total)	1
Number of poles (protected)	1
Tripping characteristic	B
Release characteristic	B
Amperage Rating	2 A
Type	FAZ Miniature circuit breaker
Technical Data - Electrical	
Voltage type	AC
Voltage rating	240 V AC / 415 V AC
Voltage rating (IEC/EN 60898-1)	240 V AC
Voltage rating (UL)	277 V
Voltage rating (UL CSA 13)	277 V AC; 48 V DC
Rated operational voltage (Ue) - max	230 V
Operational voltage (IEC/EN 60947-2) - max	254 V AC
Rated insulation voltage (Ui)	440 V
Rated impulse withstand voltage (Uimp)	4 kV
Frequency rating - min	50 Hz
Frequency rating - max	60 Hz
Rated switching capacity (IEC/EN 60947-2) at max voltage rating	10 kA
Rated switching capacity (IEC/EN 60947-2)	15 kA
Rated switching capacity (IEC/EN 60898-1)	10 kA

Breaking capacity		10 kA (UL1077)
Rated service short-circuit breaking capacity (IEC/EN 60898-1)		7.5 kA
Rated service short-circuit breaking capacity (IEC/EN 60947-2)		7.5 kA
Rated short-circuit breaking capacity (EN 60898) at 230 V		10 kA
Rated short-circuit breaking capacity (EN 60898) at 400 V		10 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V		15 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 400 V		15 kA
Overtoltage category		III
Pollution degree		2
<b>Technical Data - Mechanical</b>		
Width in number of modular spacings		1
Built-in depth		70.5 mm
Degree of protection		IP20 UL/CSA Type: - IP20 (IEC)
Connectable conductor cross section (solid-core) - min		1 mm <sup>2</sup>
Connectable conductor cross section (solid-core) - max		25 mm <sup>2</sup>
Connectable conductor cross section (multi-wired) - min		1 mm <sup>2</sup>
Connectable conductor cross section (multi-wired) - max		25 mm <sup>2</sup>
<b>Design verification as per IEC/EN 61439 - technical data</b>		
Rated operational current for specified heat dissipation (I <sub>n</sub> )		2 A
Heat dissipation per pole, current-dependent		0 W
Equipment heat dissipation, current-dependent		1.4 W
Static heat dissipation, non-current-dependent		0 W
Heat dissipation capacity		0 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		75 °C
<b>Design verification as per IEC/EN 61439</b>		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>Additional information</b>		
Current limiting class		3
Features		Additional equipment possible

Special features		Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
Used with		FAZ Miniature circuit breaker

## Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)

Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss13-27-14-19-01 [AAB905019])

Built-in depth	mm	70.5
Release characteristic		B
Number of poles (total)		1
Number of protected poles		1
Rated current	A	2
Rated voltage	V	230
Rated insulation voltage Ui	V	440
Rated impulse withstand voltage Uimp	kV	4
Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V	kA	10
Voltage type		AC
Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V	kA	10
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V	kA	15
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V	kA	15
Frequency	Hz	50 - 60
Power loss	W	1.4
Current limiting class		3
Flush-mounted installation		No
Concurrently switching neutral conductor		No
Over voltage category		3
Pollution degree		2
Additional equipment possible		Yes
Width in number of modular spacings		1
Degree of protection (IP)		IP20
Ambient temperature during operating	°C	-25 - 75
Connectable conductor cross section multi-wired	mm <sup>2</sup>	1 - 25
Connectable conductor cross section solid-core	mm <sup>2</sup>	1 - 25
Explosion-proof		No