DATASHEET - BC-U-3/36-TW-ECO



ECO Compact distribution board, flush mounting, 3-rows, 12 MU, IP40

Part no. Catalog No.

BC-U-3/36-TW-ECO 284643



Delivery program

Basic function			Basic device
Product function			Installation distribution boards
Product range			ECO DBO
Design			Flush mounted
Installation site			Indoor
Type of installation			Flush mounting
Door/Flap			White
Degree of Protection			IP40
Colour			White
Module rack			Single-rail
Shroud for protection against accidental contact			Plastic
Rows	Count		3
Module units per row			12
Description			IP40 Protection Class II Plastic housing white (RAL 9003)
Cable entries			Cable entry ribs on top and bottom
PE and N terminals design			Screw terminals
PE and N terminals	Number x cross- sectional area	mm ²	PE: 3 x (12 x 10) N: 3 x (12 x 10)
Equipment supplied			Basic device Device support rails Neutral-/protective conductor terminal

Technical data General

StandardsFileFileEN 6220s_xRoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)FileconformAmbient temperaturePC20 + 70Degree of ProtectionPCP40Protection classVeVACRated operational voltageVeVACRated frequencyfHz50Material CharacteristicsVeMS (plastic)				
Council) Image: Marcine State Ambient temperature °C °C Degree of Protection °C Pd0 Protection class Image: Marcine State Image: Marcine State Rated operational voltage Ue VAC 400 Rated frequency f Hz 50				
Degree of Protection Image: Constraint of the sector of				
Protection class Identify insulated) Rated operational voltage Ue V AC Rated frequency f Hz 50 Material characteristics F F				
Rated operational voltage Ue V AC 400 Rated frequency f Hz 50 Material characteristics F F F				
Rated frequency f Hz 50 Material characteristics				
Material characteristics				
Material ABS (plastic)				
Colour white (RAL 9003)				
Material properties				
Mechanical de la				
Impact resistance IK05				

Design verification as per IEC/EN 61439

J	
IEC/EN 61439 design verification	
10.2 Strength of materials and parts	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.


102.3.2 Verification of resistance of insulating materials to abnormal heatMeets the product standard's requirements.102.3.3 Verification of resistance of insulating materials to abnormal heat860 °C; meets the product standard's requirements.102.4 Resistance to ultra-violet (UV) radiationNot relevant to indoor installations.102.5 LiftingDes not apply to enclosures without lifting aids.102.5 LiftingNot relevant to indoor installations.102.5 LiftingNot relevant to indoor installations.102.5 LiftingNot relevant to indoor installations.102.5 IncriptionsNot relevant to indoor installations.10.3 Degree of protection of ASSEMBLIESNot relevant of sequences.10.4 Clearances and creepage distancesIs the panel builder's responsibility.10.5 Protection against electric shockProtection class 2, therefore not applicable.10.6 Incorporation of switching devices and componentsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9 Insulation propertiesIs the panel builder's responsibility.10.9 Insulation propertiesIs the panel builder's responsibility.10.9 Insulation genetors made of insulating materialMeets the product standard's requirements.10.9 Insulation genetors made of insulating materialMeets the product standard's requirements.10.9 Insulation genetors made of insulating materialMeets the product standard's requirements.10.9 Insulation genetors made of insulating materialMeets the product standard's requirements.10.9 Insulation genetors ma		
and fire due to internal electric effectsAnd relevant to indoor installations.10.2.4 Resistance to ultra-violet (UV) radiationNot relevant to indoor installations.10.2.5 LiftingDoes not apply to enclosures without lifting aids.10.2.6 Mechanical impactK0510.3.Degree of protection of ASSEMBLIESH4010.4 Clearances and creepage distancesIs the panel builder's responsibility.10.5 Protection against electric shockFrotection class 2, therefore not applicable.10.6 Incorporation of switching devices and componentsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.1 Neural electric strongthIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.1 Neural endotoresIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.1 Neural endotoresIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's requirements.10.9.1 Neural endotoresIs the product standard's requirements.10.9.1 Neural endotionsIs the panel builder is responsibility.10.10 Temperature riseIs the panel bui	10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.5 LiftingDoes not apply to enclosures without lifting aids.10.2.6 Mechanical impactK0510.2.7 InscriptionsK0510.3 Degree of protection of ASSEMBLIESP4010.4 Clearances and creepage distancesFV4010.5 Protection against electric shockFortection class 2, therefore not applicable.10.6 Incorporation of switching devices and componentsFV610.7 Internal electrical circuits and connectionsFV610.8 Connections for external conductorsFV610.9 Insulation propertiesIs the panel builder's responsibility.10.9.1 Ngulse withstand voltageIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Ingulse withstand voltageIs the panel builder's responsibility.10.9.1 Ngulse withstand voltageIs the panel builder's responsibility.10.10 Temperature riseIs the panel builder's responsibility.10.10 Temperature riseIs the panel builder's responsibility.10.11 Stort-circuit ratingIs the panel builder's responsibility.10.12 Electromagnetic compatibilityIs the panel builder's responsibility.		850 °C; meets the product standard's requirements.
10.2.6 Mechanical impactKD510.2.7 InscriptionsKB510.3 Degree of protection of ASSEMBLIESIP4010.4 Clearances and creepage distancesIs the panel builder's responsibility.10.5 Protection against electric shockIs the panel builder's responsibility.10.6 Incorporation of switching devices and componentsIs the panel builder's responsibility.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9.1 Nulation propertiesU ₁ = 400 V AC10.9.2 Power-frequency electric strengthU ₁ = 400 V AC10.9.3 Impulse withstand voltageJot Strength10.9.1 Temperature riseIs the panel builder is responsibility.10.10 Temperature riseIs the panel builder is responsibility.10.11 Short-circuit ratingIs the panel builder is responsibility.10.12 Electromagnetic compatibilityIs the panel builder is responsibility.	10.2.4 Resistance to ultra-violet (UV) radiation	Not relevant to indoor installations.
10.2.7 InscriptionsMeets the product standard's requirements.10.3 Degree of protection of ASSEMBLIESIP4010.4 Clearances and creepage distancesIs the panel builder's responsibility.10.5 Protection against electric shockProtection class 2, therefore not applicable.10.6 Incorporation of switching devices and componentsIs the panel builder's responsibility.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9 Insulation propertiesIs the panel builder's responsibility.10.9.1 Rouver-frequency electric strengthImage: Comparity of the temperature rise10.9.1 Response made of insulating materialImage: Comparity of the temperature rise calculation. Eaton will provide heat dissipation data for the devices.10.11 Short-circuit ratingImage: Comparity of the temperature rise calculation. Eaton will provide heat dissipation data for the devices.10.12 Electromagnetic compatibility.Image: Comparity of the temperature rise calculation. Eaton will provide heat dissipation data for the devices.10.12 Electromagnetic compatibilityImage: Comparity of the temperature rise calculation. Eaton will provide heat dissipation data for the devices.10.12 Electromagnetic compatibility.Image: Compatibility.10.12 Electromagnetic compatibility.Image: Compatibility.	10.2.5 Lifting	Does not apply to enclosures without lifting aids.
10.3 Degree of protection of ASSEMBLIESP4010.4 Clearances and creepage distancesis the panel builder's responsibility.10.5 Protection against electric shockProtection class 2, therefore not applicable.10.6 Incorporation of switching devices and componentsIs the panel builder's responsibility.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9 Insulation propertiesIs the panel builder's responsibility.10.9.1 Rupuse withstand voltageIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.1 Rupuse withstand voltageIs the panel builder's responsibiler responsibiler.10.10 Temperature riseIs the panel builder's responsibiler.10.11 Short-circuit ratingIs the panel builder's responsibility.10.12 Electromagnetic compatibilityIs the panel builder's responsibility.	10.2.6 Mechanical impact	IK05
10.4 Clearances and creepage distancesIs the panel builder's responsibility.10.5 Protection against electric shockProtection class 2, therefore not applicable.10.6 Incorporation of switching devices and componentsIs the panel builder's responsibility.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9 Insulation propertiesIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder is responsibility.10.9.1 Testing of enclosures made of insulating materialIs the panel builder is responsibility.10.11 Short-circuit ratingIs the panel builder's responsibility.10.12 Electromagnetic compatibility.Is the panel builder's responsibility.	10.2.7 Inscriptions	Meets the product standard's requirements.
10.5 Protection against electric shockProtection class 2, therefore not applicable.10.6 Incorporation of switching devices and componentsIs the panel builder's responsibility.10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9 Insulation propertiesIs the panel builder's responsibility.10.9.1 Supulse withstand voltageIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthIs the panel builder's responsibility.10.9.3 Impulse withstand voltageIs the panel builder is responsible for the temperature rise10.9.1 Temperature riseIs the panel builder is responsibility.10.10 Temperature riseIs the panel builder is responsibility.10.11 Short-circuit ratingIs the panel builder is responsibility.10.12 Electromagnetic compatibilityIs the panel builder's responsibility.	10.3 Degree of protection of ASSEMBLIES	IP40
10.6 Incorporation of switching devices and components Is the panel builder's responsibility. 10.7 Internal electrical circuits and connections Is the panel builder's responsibility. 10.8 Connections for external conductors Is the panel builder's responsibility. 10.9 Insulation properties Is the panel builder's responsibility. 10.9.2 Power-frequency electric strength Image: Control of Strength 10.9.3 Inpulse withstand voltage 3.75 kV 10.9.4 Testing of enclosures made of insulating material Meets the product standard's requirements. 10.10 Temperature rise The panel builder's responsibility. 10.11 Short-circuit rating Is the panel builder's responsibility. 10.12 Electromagnetic compatibility Is the panel builder's responsibility.	10.4 Clearances and creepage distances	Is the panel builder's responsibility.
10.7 Internal electrical circuits and connectionsIs the panel builder's responsibility.10.8 Connections for external conductorsIs the panel builder's responsibility.10.9 Insulation propertiesIs the panel builder's responsibility.10.9.2 Power-frequency electric strengthImage: Construction of the section o	10.5 Protection against electric shock	Protection class 2, therefore not applicable.
10.8 Connections for external conductors Is the panel builder's responsibility. 10.9 Insulation properties Is the panel builder's responsibility. 10.9.2 Power-frequency electric strength Image: Conductor Single Conducto	10.6 Incorporation of switching devices and components	Is the panel builder's responsibility.
10.9 Insulation propertiesImage: Provide the product of the devices.10.10 Temperature riseImage: Provide the product of the product of the product of the product of the devices.10.11 Short-circuit ratingImage: Provide the product of the product of the devices.10.12 Electromagnetic compatibilityImage: Provide the product of the devices.10.12 Electromagnetic compatibilityImage: Provide the product of the devices.	10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength Image: strengt Image: strengt Image: s	10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage3.75 kV10.9.4 Testing of enclosures made of insulating materialMeets the product standard's requirements.10.10 Temperature riseMeets the product standard's requirements.10.11 Short-circuit ratingImage: Compatibility10.12 Electromagnetic compatibilityImage: Compatibility	10.9 Insulation properties	
10.9.4 Testing of enclosures made of insulating material Meets the product standard's requirements. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Image: Compatibility is the panel builder's responsibility. 10.12 Electromagnetic compatibility Image: Compatibility is the panel builder's responsibility.	10.9.2 Power-frequency electric strength	U ₁ = 400 V AC
10.10 Temperature riseThe panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.10.11 Short-circuit ratingIs the panel builder's responsibility.10.12 Electromagnetic compatibilityIs the panel builder's responsibility.	10.9.3 Impulse withstand voltage	3.75 kV
10.11 Short-circuit rating Image: Compatibility compatibility 10.12 Electromagnetic compatibility Image: Compatibility compatibility	10.9.4 Testing of enclosures made of insulating material	Meets the product standard's requirements.
10.12 Electromagnetic compatibility Image: Compatibility	10.10 Temperature rise	
	10.11 Short-circuit rating	Is the panel builder's responsibility.
10.13 Mechanical function Meets the product standard's requirements.	10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
	10.13 Mechanical function	Meets the product standard's requirements.

Technical data ETIM 7.0

Distribution boards (EG000023) / Small distribution board (EC000214)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Small distribution board (ecl@ss10.0.1-27-14-24-09 [ACN387011])

Mounting method		Flush mounted (plaster)
Number of rows		3
Width in number of modular spacings		12
Type of cover		Door
Cover model		Closed
Transparent cover/door		No
Material housing		Plastic
Height	mm	550
Width	mm	303
Depth	mm	98
Built-in depth	mm	70
Internal depth	mm	90
DIN-rail		Yes
With mounting plate		No
Extension possible		No
EMC-version		No
Colour		White
RAL-number		9003
Degree of protection (IP)		IP40
With lock		No
Type of closure		Other



Additional product information (links)

IL014002Z ECO compact distribution board IL014002Z ECO compact distribution board Product overview (Web)

ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL014002ZU2014_02.pdf http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm