## Insert label, blank cam switch T0

Part no. BS45X14-T0 029416

**EL Number** 1457488

(Norway)



General specifications  Product name  Part no.  EAN  Product Length/Depth  Product height  Product width  Product weight  Certifications  Product Tradename  Product Type  Product Sub Type	Eaton Moeller® series Accessory Insert label  BS45X14-T0  4015080294160  2 millimetre  14 millimetre  45 millimetre  0.002 kilogram  UL/CSA certification not required  None  Accessory  Insert label
Part no.  EAN  Product Length/Depth  Product width  Product weight  Certifications  Product Tradename  Product Type  Product Sub Type	BS45X14-T0 4015080294160 2 millimetre 14 millimetre 45 millimetre 0.002 kilogram UL/CSA certification not required None Accessory
EAN  Product Length/Depth  Product height  Product width  Product weight  Certifications  Product Tradename  Product Type  Product Sub Type	4015080294160 2 millimetre 14 millimetre 45 millimetre 0.002 kilogram UL/CSA certification not required None Accessory
Product Length/Depth Product height Product width Product weight Certifications Product Tradename Product Type Product Sub Type	2 millimetre  14 millimetre  45 millimetre  0.002 kilogram  UL/CSA certification not required  None  Accessory
Product height Product width Product weight Certifications Product Tradename Product Type Product Sub Type	14 millimetre 45 millimetre 0.002 kilogram UL/CSA certification not required None Accessory
Product width Product weight Certifications Product Tradename Product Type Product Sub Type	45 millimetre  0.002 kilogram  UL/CSA certification not required  None  Accessory
Product weight Certifications Product Tradename Product Type Product Sub Type	0.002 kilogram  UL/CSA certification not required  None  Accessory
Certifications Product Tradename Product Type Product Sub Type	UL/CSA certification not required  None  Accessory
Product Tradename Product Type Product Sub Type	None Accessory
Product Type Product Sub Type	Accessory
Product Sub Type	,
	Insert label
Features & Functions	
Inscription	Blank (can be engraved)
General information	
Accessory/spare part type	Device labeling system
Туре	Front plates
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	50 °C
Design verification	30 0
	aw.
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal neat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.  Meets the product standard's requirements.
10.2.3.5 Resistance to ultra-violet (UV) radiation	· ·
	Meets the product standard's requirements.
10.2.5 Lifting  10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	
10.7 Internal electrical circuits and connections  10.8 Connections for external conductors	Is the panel builder's responsibility.  Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.3.4 results of enclosures made of insulating material	Not applicable.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## **Technical data ETIM 9.0**

Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switching technology (accessories) (ecl@ss13-27-37-13-92 [AKN570018])

Type of accessory/spare part	Device labeling system
Accessory	Yes
Spare part	No