

Door coupling rotary handle, black, lockable, max 60mm shaft, size 2

Part no. **NZM2-XTVDV-60-NA**
100668

General specifications		
Product name		Eaton Moeller series NZM operating element NA
Part no.		NZM2-XTVDV-60-NA
EAN		4015081005680
Product Length/Depth		75 millimetre
Product height		190 millimetre
Product width		90 millimetre
Product weight		0.72 kilogram
Compliances		UL/CSA IEC RoHS conform
Certifications		UL489 CSA (Class No. 1437-01) UL listed CE marking UL (Category Control Number DIHS) CSA certified CSA (File No. 22086) CSA-C22.2 No. 5-09 IEC60947 UL (File No. E140305)
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Operating element NA
Delivery program		
Type		Accessory Door coupling rotary handle
Features		Lockable Standard: black / gray
Special features		Complete including rotary drive and coupling parts Extension shaft additionally required. Cannot be combined with mechanical interlock For maximum shaft length 60 mm Without shaft support Cannot be combined with NZM...-XDZ additional handle External warning plate/designation label can be clipped on. Door coupling rotary handle for operating the switch through a closed control panel door
Frame		NZM2
Fitted with:		Padlock
Suitable for		Power circuit breaker Switch disconnecter
Used with		NZM2, N(S)2
Technical Data - Mechanical		
Color		Black
Cover/door type		Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door interlock not defeated in the locked OFF position. Door opens only with active rotation beyond the 0 position
Degree of protection / NEMA enclosure type		IP66 4X, 12
Lock number		Single lockable
Locking facility		With door interlock Lockable on the handle on the switch using up to 3 padlocks
Special features		Complete including rotary drive and coupling parts Extension shaft additionally required. Cannot be combined with mechanical interlock For maximum shaft length 60 mm Without shaft support Cannot be combined with NZM...-XDZ additional handle External warning plate/designation label can be clipped on. Door coupling rotary handle for operating the switch through a closed control panel door
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ec1@ss13-27-37-04-14 [AKF012019])			
With restart blockage			No
With key lock			No
Padlock locking			Yes
Colour			Black
Suitable for emergency stop			No
With extension shaft			No
Suitable for power circuit breaker			Yes
Suitable for switch disconnecter			Yes
Degree of protection (NEMA)			4X, 12