

Secondary terminal wire kit, star-delta, DILM115-150



**Part no.** DILM150-XSL  
**101487**  
**EL Number** 4137734  
**(Norway)**

General specifications		
Product name		Eaton Moeller® series DILM wiring kit
Part no.		DILM150-XSL
EAN		4015081014071
Product Length/Depth		175 millimetre
Product height		50 millimetre
Product width		120 millimetre
Product weight		1.09 kilogram
Certifications		UL Category Control No.: NLRV CSA Class No.: 2411-03, 3211-04 CSA File No.: 012528 UL 508 UL IEC/EN 60947-4-1 UL File No.: E36332 CSA-C22.2 No. 14-05 CSA CE
Product Tradename		DILM
Product Type		Accessory
Product Sub Type		Wiring kit
Features & Functions		
Functions		Main current wiring for star-delta combination
Fitted with:		Star-point bridge
General information		
Accessory/spare part type		Connecting bridge
Product category		Accessories
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		60 °C
Design verification		
Equipment heat dissipation, current-dependent P <sub>vid</sub>		17.1 W
Heat dissipation capacity P <sub>diss</sub>		0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>		5.7 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		225 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switching technology (accessories) (ecl@ss13-27-37-13-92 [AKN570018])			
Type of accessory/spare part			Connecting bridge
Accessory			Yes
Spare part			No