

Door coupling handle, EN60204

Part no. PKZ0-XH
106132

EL Number
(Norway) 4355087

General specifications	
Product name	Eaton Moeller® series PKZ0 Accessory Door coupling handle
Part no.	PKZ0-XH
EAN	4015081059027
Product Length/Depth	235 millimetre
Product height	66 millimetre
Product width	64 millimetre
Product weight	0.16 kilogram
Certifications	CSA Class No.: 3211-05 UL CE CSA File No.: 165628 UL Category Control No.: NLRV IEC/EN 60947-4-1 CSA-C22.2 No. 14 CSA UL 508 UL File No.: E36332
Product Tradename	PKZ0
Product Type	Accessory
Product Sub Type	Door coupling handle
Catalog Notes	Cannot be used in combination with VHI20-PKZ0.
Features & Functions	
Color	Black
Features	Lockable
Fitted with:	Extension shaft ON/OFF switch position and "+" (tripped), lockable 3 padlocks, 4 - 8 mm hasp thickness
General information	
Degree of protection	IP65 NEMA 4X, 12
Suitable as	Main switch to IEC/EN 60204
Used with	PKZ0-XH
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
Design verification	
Equipment heat dissipation, current-dependent P _{vid}	0 W
Heat dissipation capacity P _{diss}	0 W
Heat dissipation per pole, current-dependent P _{vid}	0 W
Rated operational current for specified heat dissipation (I _n)	0 A
Static heat dissipation, non-current-dependent P _{vs}	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.

10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])		
With restart blockage		No
With key lock		No
Padlock locking		No
Colour		Black
Suitable for emergency stop		No
With extension shaft		Yes
Suitable for power circuit breaker		No
Suitable for switch disconnecter		No
Degree of protection (NEMA)		4X, 12