

Bus termination, SmartWire-DT, for flat cable



Part no. SWD4-RC8-10
116020
EL Number 4519796
(Norway)

General specifications	
Product name	Eaton SWD4 Accessory Bus termination resistor
Part no.	SWD4-RC8-10
EAN	4015081157600
Product Length/Depth	10 millimetre
Product height	35 millimetre
Product width	49 millimetre
Product weight	0.011 kilogram
Certifications	EN 50178 CSA File No.: 2324643 UL IEC/EN 61131-2 UL File No.: E29184 CSA CSA Class No.: 3211-07 UL Category Control No.: NKCR UL CSA
Product Tradename	SWD4
Product Type	Accessory
Product Sub Type	Bus termination resistor
Features & Functions	
Functions	For the SmartWire-DT bus termination on the SmartWire-DT ribbon cable
General information	
Current consumption	17 mA
Degree of protection	IP20 (according to IEC/EN 60529, EN 50178, VBG 4) IP20
Overvoltage category	II
Pollution degree	2
Product category	SmartWire-DT accessories
Type	SmartWire-DT bus termination; plugged onto SWD4-8MF2 blade terminal at the end of the SmartWire-DT ribbon cable
Ambient conditions, mechanical	
Constant acceleration	1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations
Constant amplitude	3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations
Drop and topple	50 mm Drop height, Drop to IEC/EN 60068-2-31
Height of fall (IEC/EN 60068-2-32) - max	0.3 m
Mounting position	As required
Shock resistance	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts
Climatic environmental conditions	
Air pressure	795 - 1080 hPa (operation)
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
Ambient storage temperature - min	-40 °C
Ambient storage temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-3 Dry heat to IEC 60068-2-2
Environmental conditions	Condensation: prevent with appropriate measures
Operating temperature - min	-25 °C
Operating temperature - max	55 °C
Relative humidity	5 - 95 % (non-condensing, IEC/EN 60068-2-30)

Electro magnetic compatibility		
Air discharge		8 kV, according to IEC 61131-2, level 3, ESD
Burst impulse		1 kV, SmartWire-DT cable, according to IEC/EN 61131-2, Level 3
Contact discharge		4 kV, according to IEC/EN 61131-2, Level 2, ESD
Electromagnetic fields		3 V/m at 1.4 - 2 GHz (according to IEC/EN 61131-2:2008) 1 V/m at 2.0 - 2.7 GHz (according to IEC/EN 61131-2:2008) 10 V/m at 80 - 1000 MHz (according to IEC/EN 61131-2:2008)
Radiated RFI		10 V (IEC/EN 61131-2:2008, Level 3)
Radio interference class		Class A (EN 55011)
Electrical rating		
Power loss		0.4 W
Communication		
Connection to SmartWire-DT		Yes
Connection type		Plug, 8-pole
Input/Output		
Number of insertion cycles		200
Design verification		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0.4 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Programmable logic controllers PLC (EG000024) / Accessories/spare parts for controls (EC002584)		
Electric engineering, automation, process control engineering / Display and control component / Panel (HMI) / Panel (HMI, accessories) (ec@ss13-27-33-02-92 [AFX005008])		
Type of electrical accessory/spare part		Plug
Type of mechanical accessory/spare part		Cover
Accessory		Yes
Spare part		No