

Cover, 3p, for cable lugs, size 2



**Part no.** NZM2-XKSAE  
**119868**  
**EL Number** 4359067  
**(Norway)**

General specifications		
Product name		Eaton Moeller series NZM connection type NA
Part no.		NZM2-XKSAE
EAN		4015081177196
Product Length/Depth		93 millimetre
Product height		62 millimetre
Product width		62 millimetre
Product weight		0.102 kilogram
Compliances		IEC UL/CSA RoHS conform
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Connection type NA
Delivery program		
Type		Accessory Terminal Terminal cover
Number of poles		Three-pole
Frame		NZM2
Used with		NZM2, PN2, NS2
Technical Data - Mechanical - Terminals		
Terminal capacity (aluminum conductor)		10 mm <sup>2</sup> - 50 mm <sup>2</sup> (1x) 10 mm <sup>2</sup> - 50 mm <sup>2</sup> (2x)
Terminal capacity (copper conductor)		4 mm <sup>2</sup> - 70 mm <sup>2</sup> (2x) 10 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x)
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### Additional information

Phase separator type			Other
----------------------	--	--	-------

### Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase separation plate for power circuit breaker (EC002035)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Phase separation plate for circuit breaker (ecl@ss13-27-37-04-25 [ACN959016])

Model			Other
-------	--	--	-------