

Auxiliary contact, 1W, 2A, 250V AC



**Part no.**                    **AS AUXSC-SPM**  
**131785**  
**EL Number**                **1609772**  
**(Norway)**

General specifications		
Product name		Eaton Distribution parts
Part no.		AS AUXSC-SPM
EAN		5019586148957
Product Length/Depth		80 millimetre
Product height		65.5 millimetre
Product width		8.8 millimetre
Product weight		0.05 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Additional equipment required		Auxiliary switch
Application		Open areas Residential buildings Utility buildings
Assembly width		0.5
Device fitting		Other
EL number		1609772
Functions		Auxiliary switch
Number of contacts (change-over contacts)		1
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles at main contact unit - max		1
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		250 V
Rated switch current		2 A
Suitable for current of main contact unit - max		0 A
Type		Accessory Auxiliary contact
Used with		SPMT2PA Accessory Auxiliary contact
Voltage type		AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Other
Function		Auxiliary switch
Width in number of modular spacings		0.5
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		1
Number of fault-signal switches		0

Rated switch current	A	2
Rated voltage	V	250
Voltage type		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	A	0