## Neutral conductor, 400/630/800A



Part no. QSAN400/630/800A 1319486

Part To Same SA Accessory Manural conductor Part To SA SA SA SA SERSOR SA SA SA SERSOR SA SA SA SERSOR SA SA SA SERSOR SA	General specifications	
Fact ro.  EAM   ITTAIPETITO   EAM   ITTAIPETITO   EAM   ITTAIPETITO   Product Length Depth   Product Length Depth   Product Length Depth   Product vieth   Product vieth v		Faton OSA Accessory Neutral conductor
Product Length/Depth Product Versight Product Length/Depth Product versight Product Starting Product Startin		
Product Legipt Voleph Product Height Product Height Product weight Demonstrate Height Product veight Demonstrate D		
Product height Product width Product width Product width Product width O & Bidgeren Compliances CE Product Tandename OSA Accessory Product Tandename Product Type Accessory Product Type Roder Sub Type R		
Product width Product weight Oak kingsum Oak Cessary Product Tradenamu Product Tradenamu Accessory/Spare part type Neudral conductor Neudr		
Product weight Complanese CE Complanese CE Complanese CE Complanese Complanese Complanese Celevative Complanese Celevative Celevative Celevative Celevative Complanese Celevative Celevative Complanese Celevative Celevativ	·	
Compliances Product Tydename OSA Accessory Product Six Type Resert Information Accessory/spare part type Nountal Conductor  Climatic environmental or Mitting Type Climatic environmental conditions  Ambient operating temperature - min Equipment heat dissipation, current-dependent Pvid  Equipment heat dissipation, current-dependent Pvid  Heat dissipation or pole, current-dependent Pvid  Beat dissipation or pole, current-dependent Pvis  Both Accessory Vision of the minal stability of enclosures  Most but product standard's requirements.  102.1 Verification of thermal stability of enclosures  Most but product standard's requirements.  102.2.1 Verification of thermal stability of enclosures  102.2.1 Verification of termal stability of enclosures  102.2.1 Verification of termal stability of enclosures  102.2.2 Ministry of the stability of enclosures  102.2.3 Resistant or to vita-voide (UV) rediation  102.2.3 Resistant or to vita-voide (UV) rediation  102.2.3 Resistant or to vita-voide (UV) rediation  102.2 Resistant or to vita-voide (UV) rediation  102.2 Ministry of the stability of enclosures  102.3 Degree of protection of assemblies  102.4 Resistant or to vita-voide (UV) rediation  102.5 Ministry of the stability of enclosures  102.6 Resistant or to vita-voide (UV) rediation  102.7 Inscriptions  Meets the product standard's requirements.  102.8 Resistant or to vita-voide (UV) rediation  102.9 Resistant		
Product Tradename Product Type Accessory Product Type General information Accessory/spare part type Meutral conductor Meutral terminal Accessory/spare part type Meutral terminal Meutral terminal Accessory/spare part type Meutral terminal Meutral terminal Meutral terminal Accessory/spare part type Product Star Star Star Star Star Star Star Sta	· ·	
Product Type Product Sub Type General information Accessory/spre part type Mounting method Side mounting Type Product standard semiparature - min Ambient operating temperature - min Equipment heat dissipation, current-dependent Pvid UN Heat dissipation operating temperature - min Equipment heat dissipation, current-dependent Pvid UN Heat dissipation operating temperature - min Audient operating temperature - min Audient operating temperature - min UN Heat dissipation on operating temperature - min UN Heat dissipation operating temperature - min UN Heat dissipation on operating temperature - min UN Heat dissipation on operating temperature - min UN Static heat dissipation on on-current-dependent Pvid UN Static heat dissipation on free sistance of insulating materials to normal heat UN Static heat dissipation on free sistance of insulating materials to normal heat UN Static heat dissipation on free sistance of insulating materials to normal heat UN Static heat dissipation on free sistance of insulating materials to normal heat UN Static heat dissipation on free sistance of insulating materials to normal heat UN Static heat dissipation on free sistance of insulating materials to normal heat UN Static heat dissipation on free sistance of insulating materials to normal heat UN Static heat dissipation on free sistance of insulating materials to normal heat UN Static h		
Product Sub Type  Accessory/spare part type  Meutral terminal  Meutral terminal  Meutral terminal  Side mounting  Type  Direct neutral conductor		
General information  Accessory(spare part type  Mounting method  Side mounting  Direct neutral conductor  Ancibient operating temperature - min  Ancibient operating temperature - max  Design verification  Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  OW  Rated operational current for specified heat dissipation (n)  Static heat dissipation, concurrent-dependent Pvid  Astac heat dissipation, concurrent-dependent Pvid  Des Note in the dissipation of thermal stability of enclosures  102.21 Verification of thermal stability of enclosures  102.22 Verification of treatistance of insulating materials to normal heat  102.23 Perification of treatistance of insulating materials to normal heat  102.24 Resistance to ultra-violet (UV) radiation  102.5 Lifting  Des not apply, since the entire switchgear needs to be evaluated.  102.6 Incorporation of switching devices and components  102.7 Inscriptions  Des not apply, since the entire switchgear needs to be evaluated.  Meets the product standard's requirements.  102.6 Incorporation of assemblies  Des not apply, since the entire switchgear needs to be evaluated.  Meets the product standard's requirements.  Meets the product standard's requirements.  Meets the product standard's requirements.  103. Pogree of protection of assemblies  Des not apply, since the entire switchgear needs to be evaluated.  Meets the product standard's requirements.  Meets the product standard's requirements.  103. Pogree of protection of assemblies  Des not apply, since the entire switchgear needs to be evaluated.  Meets the product standard's requirements.  Des not apply, since the entire switchgear needs to be evaluated.  In In Internal electrical circuits and connections  Is the pan		
Accessory/spare part type Mounting method Side mounting Type Direct neutral conductor Neutral conductor Neutral conductor Neutral conductor Neutral conductor Climatic environmental conditions  Ambient operating temperature - mix 59 °C  Design verification  Equipment heat dissipation, current-dependent Pvid Neutral dissipation, current-dependent Pvid Neutral dissipation apports, current-dependent Pvid Neutral dissipation of apports, price in the dissipation of apports, current-dependent Pvid Neutral dissipation of apports, price in the dissipation of apports, current-dependent Pvid Neutral dissipation of apports, current-dependent Pvid Neutral dissipation of apports, current-dependent Pvid Neutral dissipation of apports, current for specified heat dissipation (In) Static heat dissipation, our current-dependent Pvi Neutral dissipation of apports, current dependent Pvi Neutral dissipation of apports, current for specified heat dissipation (In) Static heat dissipation, our current-dependent Pvi Neutral dissipation of apports, current dependent Pvi Neutral dissipation of apports, current dependent Pvi Neutral dissipation, current-dependent Pvi Neutral dissipation, current-dependent Pvid Neutral d	··	Neutral conductor
Mounting method  Type  Direct neutral conductor Neutral conductor Neutral conductor Neutral conductor Neutral conductor Neutral conductor Ambient operating temperature - min  Ambient operating temperature - min  Ambient operating temperature - min  Possign verification  Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  OW  Heat dissipation per pole, current-dependent Pvid  Heat dissipation per pole, current-dependent Pvid  Heat dissipation per pole, current-dependent Pvid  Batic heat dissipation, non-current-dependent Pvis  102.12 Corrosion resistance  Metats the product standard's requirements.  Metats the product standard's requirements.  102.32 Verification of thermal stability of enclosures  Metats the product standard's requirements.  102.32 Verification of resistance of insulating materials to normal heat  102.33 Resistar insul, mat, to abnormal heat/fire by internal elect. effects  102.44 Resistance to ultra-violet (IVI) radiation  102.54 Insign Desension of thermal product standard's requirements.  102.65 Uniting  Does not apply, since the entire switchgear needs to be evaluated.  102.75 Inscriptions  102.76 Inscriptions  103.76 Mechanical impact  Does not apply, since the entire switchgear needs to be evaluated.  104.76 Inscriptions  105.76 Ontoction against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  106.76 Inscriptions  107.76 Instremal electrical circuits and connections  108.76 Inscriptions of switching devices and components  109.76 Inscriptions  109	General information	
Direct neutral conductor Neutral conductor Neutral conductor Neutral conductor  Ambient operating temperature - min Ambient operating temperature - min Ambient operating temperature - max So °C  Design verification Equipment heat dissipation, current-dependent Pvid OW Heat dissipation per pole, current-dependent Pvid Peat dissipation per pole, current-dependent Pvid Assation bead dissipation per pole, current-dependent Pvid Rated operational current for specified heat dissipation (In) Static head dissipation, non-current-dependent Pvid Meat standard is requirements.  10.2.1 Verification of thermal stability of enclosures Meats the product standard's requirements.  10.2.2 Verification of thermal stability of enclosures Meats the product standard's requirements.  10.2.3 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements.  10.2.3 Verification of thermal stability of enclosures Meets the product standard's requirements.  10.2.4 Existance to ultra-volet (UV) radiation Meets the product standard's requirements.  10.2.5 Lifting Does not apply, since the entire switchpaar needs to be evaluated.  10.2.6 Mechanical impact Does not apply, since the entire switchpaar needs to be evaluated.  10.2.7 Inscriptions Meets the product standard's requirements.  10.3 Degree of protection of assemblies Does not apply, since the entire switchpaar needs to be evaluated.  10.4 Clearnaces and creepage distances Meets the product standard's requirements.  10.5 Protection against electric shock Does not apply, since the entire switchpaar needs to be evaluated.  10.6 Incorporation of switching devices and components Does not apply, since the entire switchpaar needs to be evaluated.  10.8 Connections for external conductors Is the panel builder's responsibility.  10.9 Desponsibility.  10.9 Desponsibility.  10.9 Desponsibility.  10.9 Desponsibility.  10.9 Desponsibility.  10.9 Desponsibility.  10.1 Temperature rise The panel builder's responsibility.  10.1 Temperature rise The panel bu	Accessory/spare part type	Neutral terminal
Neutral conductor	Mounting method	Side mounting
Ambient operating temperature - min Ambient operating temperature - max  50 °C  Design verification  Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation oper pole, current-dependent Pvid 25 W Rated operational current for specified heat dissipation (in) 800 A  Static heat dissipation resistance 102.2 Corrosion resistance 102.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 102.3.2 Verification of resistance of insulating materials to normal heat 102.3.2 Verification of resistance of insulating materials to normal heat 102.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects 102.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 102.5 Lifting 0 ose not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical impact 0 oses not apply, since the entire switchgear needs to be evaluated. 10.2.1 Inscriptions Meets the product standard's requirements. 10.2 General product standard's requirements. 10.3 General product standard's requirements. 10.4 Clearances and creepage distances Meets the product standard's requirements. 10.5 Protection against electric shock 0 oses not apply, since the entire switchgear needs to be evaluated. 10.6 Incorporation of switchgear needs to be evaluated. 10.7 Internal electric shock 0 oses not apply, since the entire switchgear needs to be evaluated. 10.8 Frotection against electric shock 10.9 General apply, since the entire switchgear needs to be evaluated. 10.9 Frotection of switchgear needs to be evaluated. 10.1 Internal electric strongth 10.3 Connections of resternal conductors 10.4 Flearing of enclosures made of insulating material 11.5 Protection against electric strongth 12.5 Lift panel builder's responsibility. 13.6 The panel builder's responsibility. 14.7 Internal electric strongth 15. Is the panel builder's responsibility. 15. Is the panel builder's responsibility. 16. It is the panel builder's responsibility. 17. Internal electric strongt	Туре	
Ambient operating temperature - max  Design verification  Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  OW  Heat dissipation capacity Pdiss  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvis  OW  10.22 Corrosion resistance  Meets the product standard's requirements.  10.23.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.23.2 Verification of resistance of insulating materials to normal heat  10.23.2 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.23.3 Resist of insult mat to abnormal heat/fire by internal elect. effects  10.24.4 Resistance to ultra-violet (UV) radiation  10.25 Lifting  Does not apply, since the entire switchgear needs to be evaluated.  10.27 Inscriptions  Meets the product standard's requirements.  10.28 Operating play in the entire switchgear needs to be evaluated.  10.29 Power of protection of assemblies  Does not apply, since the entire switchgear needs to be evaluated.  10.4 Clearances and creepage distances  Meets the product standard's requirements.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Connections for external conductors  In the panel builder's responsibility.  10.7 Internal electrical circuits and components  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and components  In the panel builder's responsibility.  10.8 Connections for external conductors  In the panel builder's responsibility.  10.9 Imperature rise  The panel builder's responsibility.  10.9 Imperature rise  The panel builder's responsibility.  10.9 Imperature rise  The panel builder's responsibility.  10.1 Electromagnetic compatibility  In the panel builder's responsibility.  10.1 Electromagnetic compatibility  In the panel builder's responsibility.  10.2 Power-frequency electric strength  In the p	Climatic environmental conditions	
Design verification  Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  OW  Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvid  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  OW  10.22 Corrosion resistance  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility,  10.8 Connections for external conductors  Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  10.3 Impulse withstand voltage  10.4 Electromagnetic compatibility  Is the panel builder's responsibility,  10.5 the panel builder's responsibility,  10.	Ambient operating temperature - min	-25 °C
Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  0 W  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvid  25 W  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvis  10.22 Corrosion resistance  Meets the product standard's requirements.  10.23.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.23.2 Verification of resistance of insulating materials to normal heat  10.23.3 Resist, of insul, mat. to abnormal heat/fire by internal elect. effects  Meets the product standard's requirements.  10.24 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.25 Lifting  Does not apply, since the entire switchgear needs to be evaluated.  10.27 Inscriptions  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Does not apply, since the entire switchgear needs to be evaluated.  10.4 Clearances and creepage distances  Meets the product standard's requirements.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  10.8 Connections for external conductors  Is the panel builder's responsibility.  10.9 Power-frequency electric strength  Is the panel builder's responsibility.  10.9 Power-frequency electric strength  Is the panel builder's responsibility.  The panel builder's responsibility.  The panel builder's responsibility. The specifications for the switchgear must be observed.  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	Ambient operating temperature - max	50 °C
Heat dissipation capacity Pdiss  Heat dissipation per pole, current-dependent Pvid  25 W  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  0 W  10.22 Corrosion resistance  10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of misulating materials to normal heat  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  10.2.6 Mechanical impact  10.2.7 Inscriptions  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9 Power-frequency electric strength  10.9 Resisting of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.14 Electromagnetic compatibility  10.15 Protection against electric strength  10.16 Temperature rise  10.17 Internal electrical circuits and connections  10.18 Temperature rise  10.19 Temperature rise  10.10 Temperature rise  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.14 Electromagnetic compatibility  10.15 Temperature rise  10.15 Temperature rise apple builder's responsibility. The specifications for the switchgear must be observed.  10.12 Electromagnetic compatibility	Design verification	
Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  0 W  Meets the product standard's requirements.  10.2.3 I Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3 Verification of resistance of insulating materials to normal heat  10.2.3 Verification of resistance of insulating materials to normal heat  10.2.3 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Does not apply, since the entire switchgear needs to be evaluated.  10.4 Clearances and creepage distances  Does not apply, since the entire switchgear needs to be evaluated.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9 Power-frequency electric strength  10.9 Power-frequency electric strength  10.9 Power-frequency electric strength  10.10 Temperature rise  The panel builder's responsibility.  10.10 Temperature rise  The panel builder's responsibility.  10.10 Temperature rise  The panel builder's responsibility.  10.11 Short-circuit rating  Letteromagnetic compatibility  10.12 Electromagnetic compatibility  10.14 Electromagnetic compatibility  10.15 Electromagnetic compatibility	Equipment heat dissipation, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  0 W  10.22 Corrosion resistance  10.23.1 Verification of thermal stability of enclosures  10.23.2 Verification of resistance of insulating materials to normal heat  10.23.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.24 Resistance to ultra-violet (UV) radiation  10.25 Litting  10.26 Mechanical impact  10.27 Inscriptions  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9 Ower-frequency electric strength  10.9 Testing of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.14 Electromagnetic compatibility  10.15 Electromagnetic compatibility  10.16 Incorporation of switching devices and components  10.17 Internal electrical publider's responsibility.  10.18 Is the panel builder's responsibility.  10.19 Temperature rise  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.14 Electromagnetic compatibility  10.15 Electromagnetic compatibility  10.16 Electromagnetic compatibility  10.17 Electromagnetic compatibility  10.18 Electromagnetic compatibility  10.19 Electromagnetic compatibility  10.10 Electromagnetic compatibility  10.10 Electromagnetic compatibility  10.10 Electromagnetic compatibility  10.11 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.15 Electromagnetic compatibility  10.16 Electromagnetic compatibility  10.17 Electromagnetic compatibility  10.18 Electromagnetic compatibility  10.18 Electromagnetic compatibility  10.19 Electromagnetic compatibility  10.10 Electromagnetic compatibility  10.10 Electromagnetic compatibility  10.10 Electromagnetic compatibility  10.11 Electromagnetic compatibility  1	Heat dissipation capacity Pdiss	0 W
Static heat dissipation, non-current-dependent Pvs  10.22 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Nerification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  Meets the product standard's requirements.  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Does not apply, since the entire switchgear needs to be evaluated.  10.4 Clearances and creepage distances  Meets the product standard's requirements.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material  Is the panel builder's responsibility.  10.10 Temperature rise  10.11 Short-circuit rating  Lettertomagnetic compatibility  Is the panel builder's responsibility.  10.12 Electromagnetic compatibility  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	Heat dissipation per pole, current-dependent Pvid	25 W
10.2.2 Corrosion resistance  10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of thermal stability of enclosures  10.2.3.2 Nerification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  10.2.6 Mechanical impact  10.2.7 Inscriptions  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.15 Exponsibility. The specifications for the switchgear must bill observed.	Rated operational current for specified heat dissipation (In)	800 A
10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  10.2.6 Mechanical impact  10.2.7 Inscriptions  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9 Power-frequency electric strength  10.9 Power-frequency electric strength  10.9.1 Testing of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10 see not apply, since the entire switchgear meds to be evaluated.  10.12 Electromagnetic compatibility  10.13 Estap panel builder's responsibility. The specifications for the switchgear must be observed.  10.12 Electromagnetic compatibility	Static heat dissipation, non-current-dependent Pvs	0 W
10.2.32 Verification of resistance of insulating materials to normal heat  10.2.33 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  10.2.6 Mechanical impact  10.2.7 Inscriptions  10.3 Degree of protection of assemblies  10.3 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9 Power-frequency electric strength  10.9.1 Testing of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.13 Reposed to insulating material the product standard's requirements.  Meets the product standard's requirements.  10.0es not apply, since the entire switchgear needs to be evaluated.  10.10 Temperature rise  10.10 Temperature rise panel builder's responsibility.  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.13 Short-circuit responsibility. The specifications for the switchgear must be observed.	10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.  10.2.6 Mechanical impact  Does not apply, since the entire switchgear needs to be evaluated.  10.2.7 Inscriptions  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Does not apply, since the entire switchgear needs to be evaluated.  Meets the product standard's requirements.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  The panel builder's responsibility.  10.10 Temperature rise  The panel builder's responsibility.  10.11 Short-circuit rating  Is the panel builder's responsibility.  10.10 Temperature rise  The panel builder's responsibility. The specifications for the switchgear must be observed.	10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.24 Resistance to ultra-violet (UV) radiation  10.25 Lifting  10.26 Mechanical impact  10.26 Mechanical impact  10.27 Inscriptions  10.30 Degree of protection of assemblies  10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.16 Encorporation of switching the encorporation of switching devices and components  10.10 Temperature rise product standard's requirements.  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.13 Este panel builder's responsibility. The specifications for the switchgear must be observed.  10.12 Electromagnetic compatibility  10.13 Este panel builder's responsibility. The specifications for the switchgear must be observed.	10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
Does not apply, since the entire switchgear needs to be evaluated.  10.26 Mechanical impact  Does not apply, since the entire switchgear needs to be evaluated.  10.27 Inscriptions  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  10.4 Clearances and creepage distances  Meets the product standard's requirements.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  10.8 Connections for external conductors  Is the panel builder's responsibility.  10.9.1 Power-frequency electric strength  Is the panel builder's responsibility.  10.9.2 Fower-frequency electric strength  Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  Is the panel builder is responsibility.  10.10 Temperature rise  The panel builder is responsibility.  10.11 Short-circuit rating  Is the panel builder's responsibility. The specifications for the switchgear must be observed.  10.12 Electromagnetic compatibility  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.6 Mechanical impact  10.2.7 Inscriptions  Meets the product standard's requirements.  10.3 Degree of protection of assemblies  Does not apply, since the entire switchgear needs to be evaluated.  10.4 Clearances and creepage distances  Meets the product standard's requirements.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  10.8 Connections for external conductors  Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  Is the panel builder's responsibility.  10.10 Temperature rise  The panel builder's responsibility.  10.11 Short-circuit rating  Is the panel builder's responsibility. The specifications for the switchgear must be observed.  10.12 Electromagnetic compatibility  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.7 Inscriptions  Does not apply, since the entire switchgear needs to be evaluated.  10.4 Clearances and creepage distances  Meets the product standard's requirements.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material  Is the panel builder's responsibility.  10.10 Temperature rise  The panel builder is responsibility. The specifications for the switchgear must be observed.  10.11 Short-circuit rating  Is the panel builder's responsibility. The specifications for the switchgear must be observed.  10.12 Electromagnetic compatibility  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
Does not apply, since the entire switchgear needs to be evaluated.  10.4 Clearances and creepage distances  Meets the product standard's requirements.  10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.6 Incorporation of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.  10.7 Internal electrical circuits and connections  Is the panel builder's responsibility.  10.8 Connections for external conductors  Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material  Is the panel builder's responsibility.  10.10 Temperature rise  The panel builder is responsibility. The specifications for the switchgear must be observed.  10.11 Short-circuit rating  Is the panel builder's responsibility. The specifications for the switchgear must be observed.  10.12 Electromagnetic compatibility	10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances  10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.  Is the panel builder's responsibility.  The panel builder is responsibility.  Is the panel builder is responsibility.  Is the panel builder is responsibility. The specifications for the switchgear must be observed.  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.2.7 Inscriptions	Meets the product standard's requirements.
10.5 Protection against electric shock  10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  10.8 Connections for external conductors  10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.15 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.15 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.  10.16 Is the panel builder's responsibility.  10.17 Is the panel builder's responsibility.  10.18 Is the panel builder's responsibility.  10.19 Is the panel builder is responsibility.  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.13 Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components  10.7 Internal electrical circuits and connections  1sthe panel builder's responsibility.  10.8 Connections for external conductors  1sthe panel builder's responsibility.  1sthe panel builder is responsibility.  1sthe panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  1sthe panel builder's responsibility. The specifications for the switchgear must be observed.	10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.7 Internal electrical circuits and connections  1. Is the panel builder's responsibility.  10.8 Connections for external conductors  1. Is the panel builder's responsibility.  10.9.2 Power-frequency electric strength  1. Is the panel builder's responsibility.  10.9.3 Impulse withstand voltage  1. Is the panel builder's responsibility.  10.9.4 Testing of enclosures made of insulating material  1. Is the panel builder's responsibility.  1. The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  1. Is the panel builder's responsibility. The specifications for the switchgear must be observed.  1. Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.8 Connections for external conductors  10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  Is the panel builder's responsibility.  The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.9.2 Power-frequency electric strength  10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  10.12 Electromagnetic compatibility  10.15 the panel builder's responsibility.  11.16 the panel builder is responsibility.  12.17 The panel builder is responsibility.  13.18 the panel builder's responsibility. The specifications for the switchgear must be observed.  13.19 Electromagnetic compatibility.  14.19 The panel builder's responsibility. The specifications for the switchgear must be observed.	10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage  10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  10.11 Short-circuit rating  10.12 Electromagnetic compatibility  Is the panel builder's responsibility.  The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material  10.10 Temperature rise  The panel builder is responsibility.  The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  10.11 Short-circuit rating  Is the panel builder's responsibility. The specifications for the switchgear must be observed.  10.12 Electromagnetic compatibility  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.10 Temperature rise  The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  10.11 Short-circuit rating  Is the panel builder's responsibility. The specifications for the switchgear must be observed.  10.12 Electromagnetic compatibility  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
provide heat dissipation data for the devices.  10.11 Short-circuit rating  Is the panel builder's responsibility. The specifications for the switchgear must be observed.  10.12 Electromagnetic compatibility  Is the panel builder's responsibility. The specifications for the switchgear must be observed.	10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
observed.  10.12 Electromagnetic compatibility  Is the panel builder's responsibility. The specifications for the switchgear must be	10.10 Temperature rise	
	10.11 Short-circuit rating	
	10.12 Electromagnetic compatibility	

10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## **Technical data ETIM 9.0**

Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switching technology (accessories) (ecl@ss13-27-37-13-92 [AKN570018])

Type of accessory/spare part	Neutral terminal
Accessory	Yes
Spare part	No