

Soft starter, 24 A, 200 - 480 V AC, Us= 24 V AC/DC, Frame size FS2



Part no. DS7-340SX024N0-N
134913
EL Number 4134265
(Norway)

| General specifications | |
|--------------------------------|---|
| Product name | Eaton DS7 Soft starter |
| Part no. | DS7-340SX024N0-N |
| EAN | 4015081316984 |
| Product Length/Depth | 118 millimetre |
| Product height | 150 millimetre |
| Product width | 45 millimetre |
| Product weight | 0.4 kilogram |
| Compliances | CE Marked |
| Certifications | CSA Std. C22.2 No. 0-M91 UL 508 CSA Std. C22.2 No. 14-05 IEC 60947-4-2 EN 60947-4-2 CSA-C22.2 No 0-M91 CE GB 14048.6 CSA-C22.2 No 14-05 C-Tick UL File No.: E251034 UkrSEPRO CSA22.2-14 CSA UL CSA Class No.: 321106 CSA File No.: 2511305 IEC/EN 60947-4-2 UL CSA |
| Product Tradename | DS7 |
| Product Type | Soft starter |
| Product Sub Type | None |
| Catalog Notes | Ambient Operating Temperature up to 60 at 2% derating per Kelvin temperature rise External Reversing starter solution required Regulator supply: External supply voltage |
| Features & Functions | |
| Fitted with: | Internal bypass contacts Internal bypass |
| Functions | Suppression of DC components for motors Min. ramp time 1 s - fast switching (semiconductor contactor) Single direction Suppression of closing transients Soft start function Potential isolation between power and control sections |
| General information | |
| Class | Other |
| Connection to SmartWire-DT | No |
| Degree of protection | IP20 NEMA 1 |
| Frame size | FS2 |
| Mains voltage - min | 200 V |
| Mains voltage - max | 480 V |
| Overvoltage category | II |
| Pollution degree | 2 |
| Radio interference class | Class B (EN 55011) |
| Suitable for | Branch circuits, (UL/CSA) |
| Type | Soft starter for three-phase loads |
| Voltage type | AC/DC |
| Ambient conditions, mechanical | |

| | |
|--|---|
| Mounting position | Vertical |
| Shock resistance | 8 g, 11 ms, Mechanical |
| Vibration resistance | 2M2 to EN 60721-3-2 |
| Climatic environmental conditions | |
| Altitude | Max. 2000 m Above 1000 m with 1 % derating per 100 m |
| Ambient operating temperature - min | -5 °C |
| Ambient operating temperature - max | 40 °C |
| Ambient storage temperature - min | -25 °C |
| Ambient storage temperature - max | 60 °C |
| Climatic proofing | Damp heat, constant, to IEC 60068-2-3 Damp heat, cyclic, to IEC 60068-2-30 |
| Main conducting paths | |
| Overload cycle | AC-53a: 3 - 5: 75 - 10 |
| Rated operational current (Ie) at AC-53 | 24 A |
| Rated operational voltage (Ue) - min | 230 V |
| Rated operational voltage (Ue) - max | 480 V |
| Short-circuit protection rating | PKM0-25 (+ CL-PKZ0), Type "1" coordination, Main conducting paths 3 x 170M1365, Type „2" coordination (additional with the fuses for coordination type „1"), Main conducting paths |
| Supply frequency | 50/60 Hz, fLN, Main circuit |
| Voltage rating - max | 480 V |
| Motor rating | |
| Assigned motor power at 200/208 V, 60 Hz, 3-phase | 7.5 HP |
| Assigned motor power at 220/230 V, 60 Hz, 3-phase | 7.5 HP |
| Assigned motor power at 460/480 V, 60 Hz, 3-phase | 15 HP |
| Rated operational power at 220/230 V, 50 Hz | 5.5 kW |
| Rated operational power at 400 V, 50 Hz | 11 kW |
| Terminal capacities | |
| Terminal capacity (flexible with ferrule) | 1 x (0.5 - 1.5) mm ² , Control circuit cables 2 x (0.75 - 10) mm ² , Main cables 1 x (0.75 - 16) mm ² , Main cables 2 x (0.5 - 0.75) mm ² , Control circuit cables |
| Terminal capacity (solid) | 2 x (0.75 - 10) mm ² , Main cables 1 x (0.75 - 16) mm ² , Main cables 1 x (0.5 - 2.5) mm ² , Control circuit cables 2 x (0.5 - 1.0) mm ² , Control circuit cables |
| Terminal capacity (solid/stranded AWG) | 2 x (21 - 18), Control circuit cables 18 - 6, Main cables 1 x (21 - 14), Control circuit cables |
| Terminal capacity (stranded) | 1 x (0.5 - 1.5) mm ² , Control circuit cables 2 x (0.5 - 1.0) mm ² , Control circuit cables 1 x 16 mm ² , Main cables |
| Screwdriver size | 0.6 x 3.5 mm, Terminal screws, Control circuit cables PZ2, 1 x 6 mm, Terminal screw, Standard screwdriver |
| Tightening torque | 3.2 Nm 1.2 Nm, Screw terminals, Control circuit cables |
| Control circuit | |
| Current consumption | 1.6 mA, Control circuit, Digital inputs, External 24 V 50 mA, Control circuit, Regulator supply |
| Drop-out time | 350 ms, Control circuit, Digital Inputs, DC operated |
| Drop-out voltage | AC operated: 0 - 3 V, AC operated 0 - 3 V, DC operated |
| Pick-up time | 250 ms at AC 250 ms at DC |
| Pick-up voltage | 17.3 - 27 V DC 17.3 - 27 V AC |
| Rated control supply voltage (Us) at AC, 50 Hz - min | 24 V |
| Rated control supply voltage (Us) at AC, 50 Hz - max | 24 V |
| Rated control supply voltage (Us) at AC, 60 Hz - min | 24 V |
| Rated control supply voltage (Us) at AC, 60 Hz - max | 24 V |
| Rated control supply voltage (Us) at DC - min | 24 V |
| Rated control supply voltage (Us) at DC - max | 24 V |

| Input/Output | | |
|--|--|---|
| Number of outputs | | 2 Relay Outputs (TOR, Ready) |
| Output voltage | | 250 V AC (relay outputs) |
| Protection | | Finger and back-of-hand proof, Protection against direct contact |
| Rated control voltage (Uc) | | 24 V AC 24 V AC (-15 %/+10 %) 24 V DC 24 V DC (-15 %/+10 %) |
| Rated operational current (Ie) at AC-11 | | 1 A |
| Soft start function | | |
| Application | | 1-phase motors: No 3-phase motors: Yes Soft starting of three-phase asynchronous motors |
| Delay time | | 0 - 30 s, Soft start function, Ramp times |
| Ramp/run-up time | | 1 - 30 s |
| Start voltage | | Max. 100 %, Soft start function, Start voltage = turn-off voltage Min. 30 %, Soft start function, Start voltage = turn-off voltage |
| Design verification | | |
| Equipment heat dissipation, current-dependent Pvid | | 1.1 W |
| Heat dissipation capacity Pdis | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0 W |
| Rated operational current for specified heat dissipation (In) | | 24 A |
| Static heat dissipation, non-current-dependent Pvs | | 1.1 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Soft starter (EC000640)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter (ec1@ss13-27-37-09-07 [AC0300016])

| | | |
|---|----|-----------|
| Rated operation current Ie at 40 °C Tu | A | 24 |
| Rated operating voltage Ue | V | 230 - 480 |
| Rated power three-phase motor, inline, at 230 V | kW | 5.5 |
| Rated power three-phase motor, inline, at 400 V | kW | 11 |
| Rated power three-phase motor, inside delta, at 230 V | kW | 0 |
| Rated power three-phase motor, inside delta, at 400 V | kW | 0 |

| Function | | | Single direction |
|--|--|----|------------------|
| Internal bypass | | | Yes |
| With display | | | No |
| Torque control | | | No |
| Rated surrounding temperature without derating | | °C | 40 |
| Rated control supply voltage AC 50 Hz | | V | 24 - 24 |
| Rated control supply voltage AC 60 Hz | | V | 24 - 24 |
| Rated control supply voltage DC | | V | 24 - 24 |
| Voltage type for actuating | | | AC/DC |
| Integrated motor overload protection | | | No |
| Release class | | | Other |
| Degree of protection (IP) | | | IP20 |
| Degree of protection (NEMA) | | | 1 |