

Busbar adapter, 4p, for NZM2, 250A, UL508

Part no. **NZM2-4-XAD250**
138388
EL Number **1718009**
(Norway)

General specifications			
Product name			Eaton xEffect SASY 60i MCCB adapter
Part no.			NZM2-4-XAD250
EAN			4015081351688
Product Length/Depth			35 millimetre
Product height			270 millimetre
Product width			140 millimetre
Product weight			1.8 kilogram
Compliances			RoHS conform
Product Tradename			xEffect SASY 60i
Product Type			Busbar system component
Product Sub Type			MCCB adapter
Delivery program			
Type			60 mm system Busbar adapters for NZM
Nominal current			250 A
Number of poles			Four-pole
Technical Data - Electrical			
Voltage rating at AC			690 V AC
Rated operation current (Ie)			250 A
Electric connection type			Other
Creepage resistance			CTI 200
Technical Data - Mechanical			
Rail width			30 mm
Busbar distance			60 mm
Busbar thickness - min			5 mm
Busbar thickness - max			10 mm
Busbar adapter width			140 mm
Adapter width			140 mm
Design verification as per IEC/EN 61439 - technical data			
Temperature resistance			Up to 120 °C
Additional information			
Features			Self-extinguishing acc. UL 94
Functions			Busbar adapters for NZM Component adapter for circuit breakers and switch-disconnector
Suitable for			Surface mounting on flat copper busbars 12 – 30 x 5 – 10, double T and triple T profile
Used with			NZM2(-4), PN2(-4), N2(-4)

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ecl@ss13-27-37-03-04 [ACN951016])			
Mounting rail armament			None
Type of electric connection			Other
Rated current In		A	250
Min. busbar thickness		mm	5
Max. busbar thickness		mm	10
Width of the adapter		mm	140

Rail width		mm	30
Busbar distance		mm	60