



Touch panel, 24 V DC, 5.7z, TFTcolor, ethernet, RS232, RS485, profibus, (PLC)

Part no. **XV-102-D8-57TVR-10**
 Catalog No. **142532**

EL-Nummer **4521117**
 (Norway)

Delivery program

| | | | |
|---|--|-------|--|
| Product range | | | XV100 5.7" |
| Product range | | | XV-102 |
| Function | | | HMI-PLC (SPS function, retrofittable) |
| Common features of the model series | | | Ethernet interface USB device USB Host Slot for SD card UL508, cUL approvals |
| Display - Type | | | Color display, TFT |
| Touch-technology | | | Resistive-Touch |
| Number of colours | | | 64 k Colours |
| Resolution | | Pixel | VGA 640 x 480 |
| Portrait format | | | yes |
| Screen diagonal | | Inch | 5.7 |
| Model | | | Insulating enclosure and front plate |
| Operating system | | | Windows CE 5.0 (licence incl.) |
| PLC-licence | | | Can be fitted by user with article no. 142581 LIC-PLC-MXP-COMPACT |
| License certificates for onboard interfaces | | | Can be expanded as required, see Accessories -> License product certificates |
| built-in interfaces | | | 1 x Ethernet 10/100 Mbps 1 x USB device 1 x PROFIBUS/MPI 1 x RS232 1 x RS485 1 x USB host 2.0 |
| Front type | | | Standard front with standard membrane (fully enclosed) |
| Utilization | | | Flush mounting |
| Slots | | | for SD card: 1 |
| Memory card automation | | | Optionally with SD card -> article no. 139807 |
| Pluggable communication cards (optional) | | | no |
| Touch sensor | | | Glass with film |
| Heat dissipation | | W | 9.5 |

Technical data

Display

| | | | |
|-----------------------------------|--|-------------------|--------------------------------|
| Display - Type | | | Color display, TFT |
| Screen diagonal | | Inch | 5.7 |
| Resolution | | Pixel | VGA 640 x 480 |
| Visible screen area | | mm | 115 x 86 |
| Number of colours | | | 64 k Colours |
| Contrast ratio (Normally) | | | Normally 300:1 |
| Brightness | | cd/m ² | Normally 250 |
| Back-lighting | | | LED dimnable via software |
| Service life of back-lighting | | h | Normally 40000 |
| Resistive touch protective screen | | | Touch sensor (glass with foil) |

Operation

| | | | |
|--------------|--|--|---------------------------|
| Technology | | | Resistive-Touch 4 wire |
| Touch sensor | | | Glass with film |

System

| | | | |
|-------------------------------|--|--|--|
| Processor | | | RISC CPU, 32 Bit, 400 MHz |
| Internal memory | | | DRAM (OS, Program and data memory): 64 MByte NAND-Flash (can be used for data backup): approx. 128 MByte available NVRAM (retained data): approx. 32 KByte available |
| External memory | | | SD Memory Card Slot: SDA Specification 1.00 |
| Cooling | | | Fanless CPU and system cooling, natural convection-based passive cooling |
| Back-up of real-time clock | | | |
| Battery (service life) | | | non-replaceable, CR2032 soldered in |
| Backup (time at zero voltage) | | | Normally 10 years |

Engineering

| | | | |
|--------------------------|--|--|---|
| Visualisation software | | | GALILEO EPAM XSOF-FILESYS-2 XSOF-FILESYS-3 |
| PLC-Programming software | | | XSOF-FILESYS-2 XSOF-FILESYS-3 |
| PLC-licence | | | Can be fitted by user with article no. 142581 LIC-PLC-MXP-COMPACT |
| Operating system | | | Windows CE 5.0 (licence incl.) |

Interfaces, communication

| | | | |
|---------------------|--|--|--|
| built-in interfaces | | | 1 x Ethernet 10/100 Mbps 1 x USB device 1 x PROFIBUS/MPI 1 x RS232 1 x RS485 1 x USB host 2.0 |
| USB Host | | | USB 2.0 (1.5 - 12 Mbit/s), not galvanically isolated |
| USB device | | | USB 2.0, not galvanically isolated |
| RS-232 | | | RS-232, not galvanically isolated (SUB-D plug 9 pole, UNC) |
| RS-485 | | | RS-485, not galvanically isolated (SUB-D plug 9 pole, UNC) |
| Profibus | | | PROFIBUS, not galvanically isolated, max. 1.5 MBit/s (SUB-D socket 9 pole, UNC) |
| Slots | | | for SD card: 1 |
| Ethernet | | | 100Base-TX/10Base-T |

Power supply

| | | | |
|--------------------------------------|-------------------|----|--|
| Nominal voltage | | | 24 V DC SELV (safety extra low voltage) |
| permissible voltage | | | Effective: 19.2-30.0 V DC (rated operating voltage -20%/+25%) Absolute with ripple: 18,0-31,2 V DC Battery powered: 18,0-31,2 V DC (rated operating voltage -25%/+30%) 35 V DC for a duration of < 100 ms |
| Voltage dips | | ms | ≤ 10 ms from rated voltage (24 V DC) 5 ms from undervoltage (19.2 V DC) |
| Power consumption | P _{max.} | W | 10 |
| Note on power consumption | | | Basic device USB Slave to USB Host: 2.5 Total: 9.5 |
| Heat dissipation | | W | 9.5 |
| Note on heat dissipation | | | Heat dissipation with power consumption for 24 V 7 W for basic device + 2.5 W for USB module |
| Protection against polarity reversal | | | yes |
| Type of fuse | | | Yes (fuse not accessible) |
| Potential isolation | | | no potential isolation |

General

| | | | |
|---|--|----|---|
| Housing material | | | Plastic, gray |
| Front type | | | Standard front with standard membrane (fully enclosed) |
| Dimensions (W x H x D) | | mm | 170 x 130 x 39 |
| flush mounted | | | Clearance: W x H x D ≥ 30 mm (1.18") Inclination from vertical: ±45° (if using natural convection) |
| Weight | | kg | 0.6 |
| Degree of protection (IEC/EN 60529, EN50178, VBG 4) | | | IP65 (at front), IP20 (at rear) |
| Approvals | | | |
| Approvals | | | cUL (UL508) EAC |
| Explosion protection (according to ATEX 94/9/EC) | | | II 3D Ex II T70°C IP5x: Zone 22, Category 3D |
| shipping classification | | | DNV GL |



| | | | |
|----------------------------------|--|---|---|
| Applied standards and directives | | | |
| EMC | | | (in relation to CE) EN 61000-6-2 EN 61000-6-4 EN 61131-2 |
| Product standards | | | EN 50178 EN 61131-2 |
| Security | | | EN 60950 UL 60950 |
| Mechanical shock resistance | | g | according to IEC 60068-2-27 |
| Vibration | | | according to IEC/EN 60068-2-6 |
| RoHS | | | conform |

Environmental conditions

| | | | |
|------------------------------------|--|-----|--------------------------|
| Climatic environmental conditions | | | |
| Air pressure (operation) | | hPa | 795 - 1080 |
| Temperature | | | |
| Operating ambient temperature min. | | °C | 0 |
| Operating ambient temperature max. | | °C | + 50 |
| Relative humidity | | | |
| Relative humidity | | | 10 - 95%, non-condensing |

Supply voltage U_{Aux}

| | | | |
|--------------------------------------|-----------|---|--------------------|
| Rated operational voltage | U_{Aux} | V | 24 V DC (-20/+25%) |
| Protection against polarity reversal | | | Yes |
| Potential isolation | | | No |

Supply voltage U_{Pow}

| | | | |
|--------------------------------------|-----------|---|--------------------|
| Supply voltage | U_{Pow} | V | 24 DC -20 % + 25 % |
| Input voltage ripple | | % | ≤ 5 |
| Protection against polarity reversal | | | yes |

Design verification as per IEC/EN 61439

| | | | |
|--|------------|----|--|
| Technical data for design verification | | | |
| Rated operational current for specified heat dissipation | I_n | A | 0 |
| Heat dissipation per pole, current-dependent | P_{vid} | W | 0 |
| Equipment heat dissipation, current-dependent | P_{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P_{vs} | W | 9.5 |
| Heat dissipation capacity | P_{diss} | W | 0 |
| Operating ambient temperature min. | | °C | 0 |
| Operating ambient temperature max. | | °C | 50 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | |
| | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | |
| | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | |
| | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | |
| | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | |
| | | | Please enquire |
| 10.2.5 Lifting | | | |
| | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | |
| | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | |
| | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | |
| | | | Meets the product standard's requirements. |
| 10.4 Clearances and creepage distances | | | |
| | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | |
| | | | Does not apply, since the entire switchgear needs to be evaluated. |

| | | |
|--|--|--|
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 7.0

| | | |
|--|---|-------------|
| PLC's (EG000024) / Graphic panel (EC001412) | | |
| Electric engineering, automation, process control engineering / Display and control component / Panel (HMI) / Graphic panel (HMI) (ecl@ss10.0.1-27-33-02-01 [AFX016003]) | | |
| Supply voltage AC 50 Hz | V | 0 - 0 |
| Supply voltage AC 60 Hz | V | 0 - 0 |
| Supply voltage DC | V | 20.4 - 28.8 |
| Voltage type of supply voltage | | DC |
| Number of HW-interfaces industrial Ethernet | | 1 |
| Number of interfaces PROFINET | | 0 |
| Number of HW-interfaces RS-232 | | 1 |
| Number of HW-interfaces RS-422 | | 0 |
| Number of HW-interfaces RS-485 | | 1 |
| Number of HW-interfaces serial TTY | | 0 |
| Number of HW-interfaces USB | | 2 |
| Number of HW-interfaces parallel | | 0 |
| Number of HW-interfaces Wireless | | 0 |
| Number of HW-interfaces other | | 1 |
| With SW interfaces | | Yes |
| Supporting protocol for TCP/IP | | Yes |
| Supporting protocol for PROFIBUS | | Yes |
| Supporting protocol for CAN | | No |
| Supporting protocol for INTERBUS | | No |
| Supporting protocol for ASI | | No |
| Supporting protocol for KNX | | No |
| Supporting protocol for MODBUS | | Yes |
| Supporting protocol for Data-Highway | | No |
| Supporting protocol for DeviceNet | | No |
| Supporting protocol for SUCONET | | No |
| Supporting protocol for LON | | No |
| Supporting protocol for PROFINET IO | | No |
| Supporting protocol for PROFINET CBA | | No |
| Supporting protocol for SERCOS | | No |
| Supporting protocol for Foundation Fieldbus | | No |
| Supporting protocol for EtherNet/IP | | Yes |
| Supporting protocol for AS-Interface Safety at Work | | No |
| Supporting protocol for DeviceNet Safety | | No |
| Supporting protocol for INTERBUS-Safety | | No |
| Supporting protocol for PROFIsafe | | No |
| Supporting protocol for SafetyBUS p | | No |
| Supporting protocol for other bus systems | | Yes |
| Radio standard Bluetooth | | No |
| Radio standard WLAN 802.11 | | No |

| | | |
|---|-------|-----------------|
| Radio standard GPRS | | No |
| Radio standard GSM | | No |
| Radio standard UMTS | | No |
| IO link master | | No |
| Type of display | | TFT |
| With colour display | | Yes |
| Number of colours of the display | | 65.536 |
| Number of grey-scales/blue-scales of display | | 0 |
| Screen diagonal | inch | 5.7 |
| Number of pixels, horizontal | | 640 |
| Number of pixels, vertical | | 480 |
| Useful project memory/user memory | kByte | 64 |
| With numeric keyboard | | Yes |
| With alpha numeric keyboard | | Yes |
| Number of function buttons, programmable | | 0 |
| Number of buttons with LED | | 0 |
| Number of system buttons | | 1 |
| Touch technology | | Resistive touch |
| With message indication | | Yes |
| With message system (incl. buffer and confirmation) | | Yes |
| Process value representation (output) possible | | Yes |
| Process default value (input) possible | | Yes |
| With recipes | | Yes |
| Number of password levels | | 200 |
| With printer output | | Yes |
| Number of online languages | | 100 |
| Additional software components, loadable | | Yes |
| Degree of protection (IP), front side | | IP65 |
| Degree of protection (NEMA), front side | | 4X |
| Operation temperature | °C | 0 - 50 |
| Rail mounting possible | | No |
| Wall mounting/direct mounting | | No |
| Suitable for safety functions | | No |
| Width of the front | mm | 170 |
| Height of the front | mm | 130 |
| Built-in depth | mm | 34 |

Approvals

| | | |
|--------------------------------------|--|--|
| Product Standards | | UL 60950-01; CSA-C22.2 No. 60950-1; IEC/EN 61131-2; CE marking |
| UL File No. | | E208621 |
| UL Category Control No. | | NWGQ2 |
| CSA File No. | | UL report applies to both US and Canada |
| CSA Class No. | | NWGQ8 |
| North America Certification | | UL recognized, certified by UL for use in Canada |
| Conditions of Acceptability | | The investigated Pollution Degree is: 2 The following end-product enclosures are required: Fire The unit must be supplied via a SELV source. The provided Ethernet Connection is only allowed to connect to inhouse networks. |
| Specially designed for North America | | No |
| Current Limiting Circuit-Breaker | | No |
| Degree of Protection | | IEC: IP65, UL/CSA Type: - |

Dimensions

| | | |
|------------|--|--|
| Dimensions | | |
|------------|--|--|

Additional product information (links)

| | |
|--|---|
| Instruction manual XV-102 MN04802004Z | |
| Bedienungsanleitung XV-102 MN04802004Z - Deutsch | https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN04802004Z_DE.pdf |
| Instruction manual XV-102 MN04802004Z - English | https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN04802004Z_EN.pdf |
| Quick-start manual XV100 MN04802013Z | |
| Schnellstart-Handbuch XV100 MN04802013Z - Deutsch | https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN04802013Z_DE.pdf |
| Quick-start manual XV100 MN04802013Z - English | https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN04802013Z_EN.pdf |
| User manual XSoft-CoDeSys-2, SPS programming XV100 MN04802091Z | |
| Benutzerhandbuch XSoft-CoDeSys-2, SPS-Programmierung XV100 MN04802091Z - Deutsch | https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN04802091Z-DE.pdf |
| User manual XSoft-CoDeSys-2, SPS programming XV100 MN04802091Z - English | https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN04802091Z-EN.pdf |
| Manual XSOF-CODESYS-3, SPS programming MN048008ZU | |
| Handbuch XSOF-CODESYS-3, SPS-Programmierung MN048008ZU - Deutsch | https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN048008ZU_DE.pdf |
| Manual XSOF-CODESYS-3, SPS programming MN048008ZU - English | https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN048008ZU_EN.pdf |
| f1=1454&f2=1242&f3=1773;Download Software GALILEO | http://applications.eaton.eu/sdlc?LX=11& |
| Product overview (WEB) | http://www.eaton.eu/xv |