



Lightning current and surge arresters kit, TN-S/TT kit, 3+1p

**Part no.** SPBT12-280-3+NPE-AX  
**Catalog No.** 158335  
**Alternate Catalog No.** SPBT12-280-3-NPE-AX  
**EL-Nummer (Norway)** 1609782

Similar to illustration

**Delivery program**

|                   |  |  |
|-------------------|--|--|
| Products          |  | Surge arresters  |
| Application field |  | Residential buildings<br>Utility buildings<br>Open areas |

**Technical data ETIM 7.0**

|   |                 |                               |
|---|-----------------|-------------------------------|
| Earthing, lightning and surge protection (EG000021) / Combined arrester for power supply systems (EC001457)   |                 |                               |
| Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Combined lightning current/surge arrester f. power supply s. (ecl@ss10.0.1-27-13-08-08 [ACN284011]) |                 |                               |
| System configuration DC   |                 | No                            |
| System configuration IT   |                 | Yes                           |
| System configuration TN   |                 | Yes                           |
| System configuration TN-C   |                 | No                            |
| System configuration TN-C-S   |                 | No                            |
| System configuration TN-S   |                 | Yes                           |
| System configuration TT   |                 | Yes                           |
| System configuration other  |                 | Yes                           |
| Number of poles   |                 | 4                             |
| Lightning impulse current (10/350 µs)   | kA              | 12.5                          |
| Max. continuous voltage AC  | V               | 280                           |
| Max. continuous voltage DC  | V               | 0                             |
| Nominal voltage AC  | V               | 280                           |
| Nominal voltage DC  | V               | 0                             |
| Max. PV-voltage   | V               | 0                             |
| Voltage protection level  | kV              | 0                             |
| Voltage protection level L-N  | kV              | 1.5                           |
| Voltage protection level L-PE   | kV              | 1.5                           |
| Voltage protection level N-PE   | kV              | 1.5                           |
| Voltage protection level (DC+ - DC-)  | kV              | 0                             |
| Voltage protection level (DC+/DC- - PE)   | kV              | 0                             |
| Follow current extinguishing capability   | kA              | 0                             |
| Specific energy (W/R)   | kJ/Ohm          | 2500                          |
| Max. conductor cross section solid (solid, stranded)  | mm <sup>2</sup> | 25                            |
| Max. conductor cross section flexible (fine-strand)   | mm <sup>2</sup> | 35                            |
| Mounting method   |                 | DIN rail (top hat rail) 35 mm |
| Construction size   |                 | Other                         |
| Remote signalling   |                 | No                            |
| Signalling at the device  |                 | Optic                         |
| Test class  |                 | Type 1 + 2                    |
| Exhausting  |                 | No                            |
| Integrated backup fuse  |                 | No                            |
| Energy-coordinated protection effect with regard to the terminal equipment  |                 | No                            |
| Degree of protection (IP)   |                 | IP20                          |