

Door coupling handle, for MCC-V. 90 degree, twisted



Part no. PKZ0-XHT-MCC
164297

General specifications		
Product name		Eaton Moeller® series PKZ0 Accessory Door coupling handle
Part no.		PKZ0-XHT-MCC
EAN		4015081608256
Product Length/Depth		235 millimetre
Product height		66 millimetre
Product width		64 millimetre
Product weight		0.16 kilogram
Certifications		EN 60204
Product Tradename		PKZ0
Product Type		Accessory
Product Sub Type		Door coupling handle
Catalog Notes		Cannot be used in combination with VHI20-PKZ0.
Features & Functions		
Color		Black
Features		Lockable
Fitted with:		Axis extension Door interlock ON/OFF switch position and "+" (tripped), lockable 3 padlocks, 4 - 8 mm hasp thickness
General information		
Degree of protection		NEMA Other
Suitable as		Main switch to EN 60204 in MCC power distribution systems and with PKZM0 installed when rotated by 90°
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		55 °C
Design verification		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.

10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Door coupling handle for switchgear (EC000230)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Hand drive for switch devices (ec1@ss13-27-37-04-15 [AKF013019])			
With axis extension			Yes
With door interlock			Yes
Lockable			Yes
With handle red/yellow			No
Degree of protection (NEMA)			Other