

**Trip block, 30 - 65 A, System protection, Connection to SmartWire-DT: no,
For use with: PKE65 basic device**

Part no. PKE-XTUCP-65

168798

EL Number

4315142

(Norway)

General specifications	
Product name	Eaton Moeller® series PKE Trip block
Part no.	PKE-XTUCP-65
EAN	4015081652891
Product Length/Depth	84.4 millimetre
Product height	69.9 millimetre
Product width	55 millimetre
Product weight	0.238 kilogram
Certifications	IEC/EN 60947 VDE 0660
Product Tradename	PKE
Product Type	Accessory
Product Sub Type	Trip block
Features & Functions	
Functions	Line and cable protection System protection Overcurrent protection Short-circuit protection
Number of poles	Three-pole
General information	
Current flow times - min	1000 (Class 20) AC-4 cycle operation, Main conducting paths 500 (Class 5) AC-4 cycle operation, Main conducting paths 700 (Class 10) AC-4 cycle operation, Main conducting paths 900 (Class 15) AC-4 cycle operation, Main conducting paths Note: Going below the minimum current flow time can cause overheating of the load (motor). For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.
Cut-out periods - min	≤ 500 ms, main conducting paths, AC-4 cycle operation
Degree of protection	Device: IP20 Terminals: IP00
Operating frequency	60 Operations/h
Overload release current setting - min	30 A
Overload release current setting - max	65 A
Overvoltage category	III
Pollution degree	3
Product category	Accessories
Protection	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)	6000 V AC
Temperature compensation	-25 - 55 °C, Operating range -5 - 40 °C to IEC/EN 60947, VDE 0660
Voltage type	Self powered
Ambient conditions, mechanical	
Shock resistance	15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Climatic environmental conditions	
Altitude	Max. 2000 m
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
Ambient operating temperature (enclosed) - min	25 °C
Ambient operating temperature (enclosed) - max	40 °C
Ambient storage temperature - min	40 °C

Ambient storage temperature - max		80 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Electrical rating		
Rated frequency - min		50 Hz
Rated frequency - max		60 Hz
Rated operational current (Ie)		65 A
Rated operational voltage (Ue) at AC - max		690 V
Rated uninterrupted current (Iu)		65 A
Short-circuit rating		
Short-circuit release		± 20% tolerance, Trip blocks Trip block adjustable 5 - 8 x Ir Delayed approx. 60 ms, Trip blocks 150 - 520 A, Irm, Setting range
Magnet system		
Rated control supply voltage (Us) at AC, 50 Hz - min		0 V
Rated control supply voltage (Us) at AC, 50 Hz - max		0 V
Rated control supply voltage (Us) at AC, 60 Hz - min		0 V
Rated control supply voltage (Us) at AC, 60 Hz - max		0 V
Rated control supply voltage (Us) at DC - min		0 V
Rated control supply voltage (Us) at DC - max		0 V
Communication		
Connection to SmartWire-DT		No
Design verification		
Equipment heat dissipation, current-dependent Pvid		9.3 W
Heat dissipation capacity Pdiss		0 W
Heat dissipation per pole, current-dependent Pvid		3.1 W
Rated operational current for specified heat dissipation (In)		65 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Trip block for power circuit-breaker (EC000617)

Type of motor protection			Electronic release
Number of poles			3
Rated permanent current I _u		A	65
Rated switch current		A	
Overload release current setting		A	30 - 65
Short-circuit release function			Delayed
Current setting delayed short-circuit release		A	
Current setting undelayed short-circuit release		A	
With ground fault protection function			No
External power supply required			No
Voltage type (supply voltage)			
Supply voltage AC 50 Hz		V	
Supply voltage AC 60 Hz		V	
Supply voltage DC		V	
Number of auxiliary contacts as normally closed contact			
Number of auxiliary contacts as normally open contact			
Number of auxiliary contacts as change-over contact			
Voltage type (operating voltage)			
Operating voltage AC 50 Hz		V	
Operating voltage AC 60 Hz		V	
Operating voltage DC		V	
Width		mm	55
Height		mm	69.9
Depth		mm	84.4