

**Variable frequency drive, 400 V AC, 3-phase, 30 A, 15 kW, IP55/NEMA 12,
Radio interference suppression filter, OLED display**



Part no. DA1-34030FB-B55C
169391
EL Number 4137313
(Norway)

General specifications	
Product name	Eaton DA1 Variable frequency drive
Part no.	DA1-34030FB-B55C
EAN	4015081658343
Product Length/Depth	240 millimetre
Product height	450 millimetre
Product width	173 millimetre
Product weight	11.5 kilogram
Certifications	UL File No.: E172143 UL Category Control No.: NMMS, NMMS7 UL 508C EAC CUL RCM UL Specification for general requirements: IEC/EN 61800-2 UkrSEPRO RoHS, ISO 9001 CE Safety: EN 61800-5-1: 2003 UL report applies to both US and Canada DNV CSA-C22.2 No. 14 Certified by UL for use in Canada IEC/EN 61800-3 IEC/EN61800-3 IEC/EN61800-5
Product Tradename	DA1
Product Type	Variable frequency drive
Product Sub Type	None
Catalog Notes	The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request.
General information	
Cable length	C2 ≤ 5 m, Radio interference level, maximum motor cable length C3 ≤ 25 m, Radio interference level, maximum motor cable length 100 m, screened, maximum permissible, Motor feeder 150 m, unscreened, maximum permissible, Motor feeder 200 m, screened, with motor choke, maximum permissible, Motor feeder 300 m, unscreened, with motor choke, maximum permissible, Motor feeder
Communication interface	DeviceNet, optional Modbus-TCP, optional EtherCAT, optional SmartWire-DT, optional OP-Bus (RS485), built in PROFIBUS, optional CANopen®, built in Modbus RTU, built in Ethernet IP, optional PROFINET, optional
Connection to SmartWire-DT	In conjunction with DX-NET-SWD1 SmartWire DT module Yes
Degree of protection	NEMA 12 IP55
Electromagnetic compatibility	1st and 2nd environments (according to EN 61800-3)
Fitted with:	Control unit Additional PCB protection Internal DC link PC connection Radio interference suppression filter Brake chopper OLED display Breaking resistance IGBT inverter
Frame size	FS4

Functions		4-quadrant operation possible
Mounting position		Vertical
Product Category		Variable frequency drives
Protection		Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
Protocol		MODBUS EtherNet/IP DeviceNet PROFINET IO PROFIBUS Other bus systems CAN TCP/IP
Safety function/level		STO (Safe Torque Off, SIL2, PLc Cat 2)
Suitable for		Branch circuits, (UL/CSA)
Radio interference class		C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary. Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
Climatic environmental conditions		
Ambient operating temperature - min		-10 °C
Altitude		Above 1000 m with 1 % derating per 100 m Max. 1000 m Max. 4000 m
Ambient operating temperature - max		40 °C
Ambient operating temperature at 150% overload - min		-10 °C
Ambient operating temperature at 150% overload - max		40 °C
Ambient storage temperature - min		-40 °C
Ambient storage temperature - max		60 °C
Climatic proofing		< 95 average relative humidity (RH), no condensation, no corrosion
Main circuit		
Efficiency		97.5 % (η)
Heat dissipation at current/speed		136 W at 25% current and 0% speed 165 W at 25% current and 50% speed 165 W at 50% current and 0% speed 194 W at 50% current and 50% speed 216 W at 50% current and 90% speed 278 W at 100% current and 0% speed 323 W at 100% current and 50% speed 359 W at 100% current and 90% speed
Input current ILN at 150% overload		34.2 A
Leakage current at ground IPE - max		2.47 mA
Mains switch-on frequency		Maximum of one time every 30 seconds
Mains voltage - min		380 V
Mains voltage - max		480 V
Operating mode		Sensorless vector control (SLV) U/f control Optional: Vector control with feedback (CLV) Speed control with slip compensation
Output frequency - min		0 Hz
Output frequency - max		500 Hz
Output voltage (U2)		400 V AC, 3-phase 480 V AC, 3-phase
Overload current IL at 150% overload		45 A
Rated control supply voltage		10 V DC (Us, max. 10 mA)
Rated frequency - min		48 Hz
Rated frequency - max		62 Hz
Rated operational current (Ie) at 150% overload		30 A
Rated operational power at 380/400 V, 50 Hz, 3-phase		15 kW
Rated operational voltage		480 V AC, 3-phase 400 V AC, 3-phase
Resolution		0.1 Hz (Frequency resolution, setpoint value)
Short-circuit protection rating		50 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring
Starting current - max		200 %, IH, max. starting current (High Overload), for 4 seconds every 40 seconds, Power section

Supply frequency		50/60 Hz
Switching frequency		8 kHz, 4 - 24 kHz adjustable (audible), fPWM, Power section, Main circuit
System configuration type		AC supply systems with earthed center point
Voltage rating - max		480 V AC
Motor rating		
Assigned motor current IM at 400 V, 50 Hz, 150% overload		29.3 A
Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload		27 A
Assigned motor power at 460/480 V, 60 Hz, 3-phase		20 HP
Apparent power		
Apparent power at 400 V		20.78 kV-A
Apparent power at 480 V		24.94 kV-A
Braking function		
Braking resistance		22 Ω
Braking torque		Max. 30 % MN, Standard - Main circuit Max. 100 % of rated operational current Ie, variable, DC - Main circuit Max. 100 % of rated operational current Ie with external braking resistor - Main circuit
Switch-on threshold for the braking transistor		780 V DC
Control circuit		
Number of inputs (analog)		2
Number of inputs (digital)		5
Number of outputs (analog)		2
Number of outputs (digital)		2
Number of relay outputs		2 (parameterizable, 1 N/O and 1 changeover contact, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))
Rated control voltage (Uc)		24 V DC (external, max. 100 mA)
Design verification		
Equipment heat dissipation, current-dependent Pvid		375 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		30 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Frequency converter =< 1 kV (EC001857)		
Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency / Servo converter = < 1 kV (ecl@ss13-27-02-31-01 [AKE177019])		
Mains voltage	V	380 - 480
Mains frequency		50/60 Hz
Number of phases input		3
Number of phases output		3
Max. output frequency	Hz	500
Max. output voltage	V	500
Nominal output current I2N	A	30
Max. output at quadratic load at rated output voltage	kW	15
Max. output at linear load at rated output voltage	kW	15
Power consumption	W	375
Relative symmetric net frequency tolerance	%	10
Relative symmetric net voltage tolerance	%	10
Number of analogue outputs		2
Number of analogue inputs		2
Number of digital outputs		2
Number of digital inputs		5
With control element		Yes
Application in industrial area permitted		Yes
Application in domestic- and commercial area permitted		Yes
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		Yes
Supporting protocol for CAN		Yes
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		Yes
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		Yes
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		Yes
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for BACnet		No
Supporting protocol for other bus systems		Yes
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		1
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		0
Number of HW-interfaces parallel		0
Number of HW-interfaces other		0
With optical interface		No

With PC connection			Yes
Integrated breaking resistance			Yes
4-quadrant operation possible			Yes
Type of converter			U converter
Degree of protection (IP)			IP55
Degree of protection (NEMA)			12
Height		mm	450
Width		mm	173
Depth		mm	240