

Mini compact distribution board, 1-row 5 SU, IP30



Part no. MINI-5-ST
177074
EL Number 1702979
(Norway)

General specifications		
Product name		Eaton xComfort Micro/Mini mini series
Part no.		MINI-5-ST
EAN		4015081715176
Product Length/Depth		83 millimetre
Product height		140 millimetre
Product width		120 millimetre
Product weight		0.16 kilogram
Compliances		RoHS conform
Certifications		IEC/EN 62208
Product Tradename		xComfort Micro/Mini
Product Type		Mini series
Product Sub Type		None
Delivery program		
Type		Basic device Installation distribution board MINI distribution board
Application		Indoor (installation site)
Color		Signal white (RAL 9003) White
Technical Data - Electrical		
Voltage rating at AC		400 V AC
Frequency rating of contacts		50 Hz
Technical Data - Mechanical		
Closure type		Other
Enclosure material		Plastic
Width in number of modular spacings		5
Mounting method		DIN-rail Surface mounted (plaster) Surface mounting
Material		ABS (plastic)
Degree of protection		IP30 IK05 (impact resistance)
Number of module space units per row		5
Number of rows		1
Terminal type		Screw terminals
PE and N terminal number and cross section		N: 1 x 16 mm ²
Built-in depth		70 mm
Built-in height		0 mm
Built-in width		0 mm
Internal depth		60 mm
Cover/door color		Transparent
Cover/door model		Closed
Cover/door type		Door Single
Module rack type		Single-rail
Protective shrouding material		Plastic
Temperature-rise verification as per IEC 60890		
Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890)		11 W
Heat diss. ambient 35°C delta T:35°C wall mount individ. encl. top (IEC 60890)		13 W
Design verification as per IEC/EN 61439 - technical data		

Ambient operating temperature details			-5 °C - 40 °C
Design verification as per IEC/EN 61439			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			650 °C; meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Not relevant to indoor installations.
10.2.5 Lifting			Does not apply to enclosures without lifting aids.
10.2.6 Mechanical impact			IK05
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			IP30
10.4 Clearances and creepage distances			Is the panel builder's responsibility.
10.5 Protection against electric shock			Protection class 2, therefore not applicable.
10.6 Incorporation of switching devices and components			Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			U _i = 400 V AC
10.9.3 Impulse withstand voltage			2.8 kV
10.9.4 Testing of enclosures made of insulating material			Meets the product standard's requirements.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			Meets the product standard's requirements.
Additional information			
Features			EMC-version
Fitted with:			Basic device Neutral-/protective conductor terminal
Functions			Basic device
Protection class			II (totally insulated)
RAL-number			9003
Special features			IP30 Protection Class II Plastic housing white (RAL 9003)
Used with			MINI distribution board Installation distribution board Basic device

Technical data ETIM 9.0

Distribution boards (EG000023) / Small distribution board (EC000214)			
Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (including small distribution board) / Small distribution board (ecl@ss13-27-14-24-09 [ACN387016])			
Mounting method			Surface mounted
Number of rows			1
Width in number of modular spacings			5
Type of covering			Door
Cover model			Closed
Type of door			Single
Transparent cover/door			Yes
Signal passing door			No
With lock			No
Type of closure			Other
Housing material			Plastic
Built-in depth		mm	70
Built-in height		mm	0
Built-in width		mm	0
Inner depth		mm	60
Earthing terminal block			No
Neutral terminal block			No

DIN-rail			Yes
With mounting plate			No
Extension possible			No
EMC-version			Yes
UV resistant			No
Colour			White
RAL-number			9003
Degree of protection (IP)			IP30
Height		mm	140
Width		mm	120
Depth		mm	83