

Lightning current / surge arresters, SPD insert, 600 VDC

Part no. **SPPVT12-06**
177259

General specifications		
Product name		Eaton Moeller series xPole - SPPVT2.12 Surge Protection Device
Part no.		SPPVT12-06
EAN		4015081717118
Product Length/Depth		43.3 millimetre
Product height		52.2 millimetre
Product width		17.5 millimetre
Product weight		0.07 kilogram
Compliances		RoHS conform
Product Tradename		xPole - SPPVT2.12
Product Type		Surge Protection Device
Product Sub Type		None
Delivery program		
Application		Open areas Residential buildings Utility buildings
Type		DC overvoltage protection Surge arrester
Technical Data - Electrical		
Connection		For ungrounded systems
Voltage rating (Iu) - max		600 V
Voltage protection level		1.7 kV
Voltage protection level (L-N)		0 kV
Voltage protection level (N-PE)		0 kV
Nominal voltage at AC		0 V
Nominal voltage at DC		300 V
Continuous voltage at AC - max		0 V
Continuous voltage at DC - max		360 V
PV-voltage - max		360 V
Nominal discharge surge current (8/20)		15 kA
Discharge surge current (8/20) - max		0 kA
Short-circuit breaking capacity (ISCCR)		0 kA
Signalling at the device		Optic
Technical Data - Mechanical		
Frame		1 modular spacing
Mounting method		On basic element
Number of conductors without earthing		0
Conductor cross section (flexible, fine-strand) - min		0 mm ²
Conductor cross section (flexible, fine-strand) - max		0 mm ²
Conductor cross section (solid, solid-strand) - min		0 mm ²
Conductor cross section (solid, solid-strand) - max		0 mm ²
Degree of protection		IP20
Design verification as per IEC/EN 61439 - technical data		
Rated operational current for specified heat dissipation (I _n)		0 A
Heat dissipation per pole, current-dependent		0 W
Equipment heat dissipation, current-dependent		0 W
Static heat dissipation, non-current-dependent		0.01 W
Heat dissipation capacity		0 W
Ambient operating temperature - min		-40 °C
Ambient operating temperature - max		80 °C
Additional information		

Features		Category type 2
Special features		Pluggable
System configuration type		IT

Technical data ETIM 9.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)		
Electric engineering, automation, process control engineering / Internal and external lightning protection / Lightning protection (other) / Lightning protection (other, not specified) (ecl@ss13-27-17-90-90 [AHE465002])		
System configuration DC		No
System configuration IT		Yes
System configuration TN		No
System configuration TN-C		No
System configuration TN-C-S		No
System configuration TN-S		No
System configuration TT		No
System configuration other		No
Number of conductors (without earthing)		0
Nominal discharge surge current (8/20)	kA	15
Max. discharge surge current (8/20)	kA	0
Nominal voltage AC	V	0
Nominal voltage DC	V	300
Max. continuous voltage AC	V	0
Max. continuous voltage DC	V	360
Max. PV-voltage	V	360
Voltage protection level	kV	1.7
Voltage protection level L-N	kV	0
Voltage protection level N-PE	kV	0
Max. overcurrent protection device, parallel connection (fuse)	A	0
Max. overcurrent protection device, series connection (fuse)	A	0
Short-circuit breaking capacity (Isc cr)	kA	0
Integrated short-circuit protection		No
Integrated short-circuit protection selective to fuse gG	A	0
Integrated backup fuse		No
Leakage-current free		No
Mounting method		On basic element
Construction size		1 modular spacing
Max. conductor cross section solid (solid, stranded)	mm ²	0
Max. conductor cross section flexible (fine-strand)	mm ²	0
With remote signalling contact		No
Signalling at the device		Optical
Category type 2		Yes
Degree of protection (IP)		IP20