



Combination plug-in terminal KSK; individual; blue for neutral conductor



Powering Business Worldwide™

Part no. KSK-N
Catalog No. 178903

Delivery program

Basic function		Accessory consideration
Accessories		General
Product range		KLV DBO
Degree of Protection		IP2X

Technical data ETIM 7.0

Terminal blocks (EG000012) / Single- and multi-pole terminal strip (EC001284)		
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Single- and multi-pole terminal strip (ecl@ss10.0.1-27-14-11-06 [AAB921016])		
Drill hole distance centrally	mm	1
Explosion-tested version 'Ex e'		No
Connectable conductor cross section fine-strand without cable end sleeve	mm ²	2.5 - 25
Connectable conductor cross section fine-strand with cable end sleeve	mm ²	2.5 - 16
Connectable conductor cross section solid-core	mm ²	2.5 - 25
Connectable conductor cross section multi-wired	mm ²	2.5 - 25
Rated current I _n	A	63
Rated voltage	V	400
Type of electrical connection 1		Screw connection
Type of electrical connection 2		Plug-in connection
Connection position		Inclined
Number of poles		1
Number of clamp positions per pole		8
Mounting method		Direct mounting
Material insulation body		Thermoplastic
Operation temperature	°C	35 - 35
Inflammability class of insulation material acc. with UL94		V0
Width/grid dimension	mm	55
Height at lowest possible mounting height	mm	17
Length	mm	19.5
Closing plate required		No
Colour		Blue
Transparent		No

Additional product information (links)

Product overview (Web)	http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm
------------------------	---