## IP23 enclosures, For use with STZ13.3



Part no. +IP23/06 200649

General specifications	
Product name	Eaton Moeller® series Accessory Housing
Part no.	+IP23/06
EAN	4015082006495
Product Length/Depth	310 millimetre
Product height	540 millimetre
Product width	690 millimetre
Product weight	14.8 kilogram
Compliances	CE
Product Tradename	None
Product Type	Accessory
Product Sub Type	Housing
Catalog Notes	Electrical characteristics: all details for no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values relate to a temperature of 20 $^{\circ}\text{C}$
Features & Functions	
Enclosure material	Steel
Features	Separate windings
General information	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	40 °C
Degree of protection	IP23 NEMA Other
Duty factor	100 %
Insulation class	B F
Model	Built-in
Product category	Accessories
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	360 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
Radiated heat dissipation with separate mounting	360 W (at an ambient temperature of 20 °C)
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## **Technical data ETIM 9.0**

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss13-27-37-13-01 [AKN343019])

Width         mm         690           Height         mm         540           Depth         mm         310           With transparent cover         No         No           Suitable for emergency stop         No         No           Model         Built-in           Degree of protection (IP)         IP23	(ECISS 10-27-07-10-01 [AICHOUTO])			
Height         mm         540           Depth         mm         310           With transparent cover         No         No           Suitable for emergency stop         No         No           Model         Built-in           Degree of protection (IP)         IP23	Housing material		Steel	
Depth         mm         310           With transparent cover         No           Suitable for emergency stop         No           Model         Built-in           Degree of protection (IP)         IP23	Width	mm	690	
With transparent cover No Suitable for emergency stop No Model Built-in Degree of protection (IP) IP23	Height	mm	540	
Suitable for emergency stop  Model  Degree of protection (IP)  No  IP23	Depth	mm	310	
Model Built-in Degree of protection (IP) IP23	With transparent cover		No	
Degree of protection (IP)	Suitable for emergency stop		No	
	Model		Built-in	
Degree of protection (NEMA) Other	Degree of protection (IP)		IP23	
	Degree of protection (NEMA)		Other	