



Key, MS2-20, according to data




Part no. **M22-ES-MS***
 Catalog No. **216417**
 Alternate Catalog No. **-**
 EL-Nummer **4355424**
 (Norway)

Delivery program

| | | | |
|----------------------------|--|--|--|
| Basic function accessories | | | Individual keys |
| Description | | | Lock mechanism MS2 – MS20 |
| Degree of Protection | | | None |
| Connection to SmartWire-DT | | | no |
| For use with | | | M22(S)-W(R)S(3)-MS*... |
| Note asterisk part number | | | Please configure the asterisks in the cart |

Technical data

General

| | | | |
|-------------------------|--|----|--|
| Degree of Protection | | | None |
| Ambient temperature | | | |
| Open | | °C | -25 - +70 |
| shipping classification | | | DNV GL LR |
| | | |    |

Design verification as per IEC/EN 61439

| | | | |
|--|--|----|-----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 70 |

Technical data ETIM 7.0

| | | | |
|---|--|--|-------|
| Low-voltage industrial components (EG000017) / Accessories for control circuit devices (EC002024) | | | |
| Type of electrical accessory | | | Other |
| Type of mechanical accessory | | | Key |

Approvals

| | | | |
|-----------------------------|--|--|-----------------------------------|
| North America Certification | | | UL/CSA certification not required |
|-----------------------------|--|--|-----------------------------------|