

Telescopic adapters

Part no. M22-TA
226161
EL Number 4355796
(Norway)

| General specifications | | |
|--|--|--|
| Product name | | Eaton Moeller® series M22 Accessory Telescopic clip |
| Part no. | | M22-TA |
| EAN | | 4015082261610 |
| Product Length/Depth | | 80 millimetre |
| Product height | | 40 millimetre |
| Product width | | 45 millimetre |
| Product weight | | 0.043 kilogram |
| Compliances | | CE Marked |
| Certifications | | EN 60947-5 IEC 60947-5 CSA Std. C22.2 No. 94-91 CSA Std. C22.2 No. 14-05 UL 508 VDE CSA UL CE IEC/EN 60947-5 CSA File No.: 012528 UL File No.: E29184 CSA Class No.: 3211-03 CSA-C22.2 No. 14-05 UL Category Control No.: NKCR CSA-C22.2 No. 94-91 |
| Product Tradename | | M22 |
| Product Type | | Accessory |
| Product Sub Type | | Telescopic clip |
| Catalog Notes | | Do not use in conjunction with emergency switching off actuators. Infinitely adjustable from 75 to 115 mm through scales maximum of 10 x M22-TC brackets per enclosure, five of which can hold stay-put actuators Steplessly adjustable, screw- and snap fixing (top-hat rail IEC/EN 60715). |
| Features & Functions | | |
| Fitted with: | | 35 mm top-hat rail (according to IEC/EN 60715) |
| Functions | | For equalization of the mounting depth of rear mounting devices in CI enclosures, and in cabinets with mounting depths of 115 - 155 mm For mounting of EASY, FAZ, PKZ, DIL etc. weighing ≤ 0.3 kg |
| General information | | |
| Accessory/spare part type | | Accessory |
| Product category | | Accessories Compact PLCs Control relay easyRelay |
| Used with | | PKE EC4P easy200/500/700/800 PKZM0 MFD-CP8 |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 70 °C |
| Communication | | |
| Connection to SmartWire-DT | | No |
| Design verification | | |
| Equipment heat dissipation, current-dependent P _{vid} | | 0 W |
| Heat dissipation capacity P _{diss} | | 0 W |
| Heat dissipation per pole, current-dependent P _{vid} | | 0 W |
| Rated operational current for specified heat dissipation (I _n) | | 0 A |

| | | | |
|--|--|--|--|
| Static heat dissipation, non-current-dependent Pvs | | | 0 W |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Please enquire |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | Not applicable. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | | |
|--|--|--|-------|
| Low-voltage industrial components (EG000017) / Accessories/spare parts for command devices (EC002024) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Command and alarm device (accessories) (ecl@ss13-27-37-12-92 [AC0037015]) | | | |
| Type of electrical accessory/spare part | | | Other |
| Type of mechanical accessory/spare part | | | Other |
| Accessory | | | Yes |
| Spare part | | | No |