

## Shunt release, 12-110V, 1HP

**Part no.** ZP-ASA/24  
**248438**  
**EL Number** 1609470  
**(Norway)**

General specifications		
Product name		Eaton Distribution parts
Part no.		ZP-ASA/24
EAN		4015082484385
Product Length/Depth		80 millimetre
Product height		75 millimetre
Product width		26.2 millimetre
Product weight		0.087 kilogram
Compliances		RoHS conform
Certifications		IEC 61373 EN45545-2
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		Shunt release
Additional equipment required		Shunt release (for power circuit breaker)
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Application		Switchgear for industrial and advanced commercial applications
Assembly width		1
Device fitting		Other
EL number		1609470
Functions		Shunt release (for power circuit breaker)
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles at main contact unit - max		1
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		24 V
Rated switch current		0 A
Suitable for current of main contact unit - max		15 A
Type		Accessory Accessory for combined residual current/power circuit breaker Accessory for miniature circuit breaker
Used with		Shunt releases Accessory Accessory for combined residual current/power circuit breaker Accessory for miniature circuit breaker
Voltage type		AC

## Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Other
Function		Shunt release (for power circuit breaker)
Width in number of modular spacings		1

Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0
Rated voltage		V	24
Voltage type			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			1
Suitable for max. current main contact unit		A	15