

Auxiliary contact, 2early N/O, operates as an early-make contact, 3m cable

Part no. NZM1-XHIVL

259432

EL Number

4358869

(Norway)

General specifications		
Product name		Eaton Moeller series NZM auxiliary contact
Part no.		NZM1-XHIVL
EAN		4015082594329
Product Length/Depth		37 millimetre
Product height		66 millimetre
Product width		32 millimetre
Product weight		0.15 kilogram
Compliances		RoHS conform
Certifications		UL (Category Control Number DIHS) CSA certified UL listed CE marking CSA (Class No. 1437-01) CSA-C22.2 No. 5-09 IEC60947 CSA (File No. 22086) UL489 UL (File No. E140305)
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Auxiliary contact
Delivery program		
Special features		C300/R300 (auxiliary contacts, UL/CSA, pilot duty)
Used with		FAZ-B6 (max. miniature circuit breaker)
Technical Data - Electrical		
Voltage rating at DC		220 V DC
Voltage rating at AC		500 V AC
Rated operational current		1 A at 250 V DC (UL/CSA) 2.5 A at 240 V AC (UL/CSA)
Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V		4 A
Conventional thermal current Ith of auxiliary contacts		4 A
Fuse short-circuit protection - max		10 A gG/gL
Technical Data - Mechanical		
Mounting Method		Other
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		2
Connection type		Screw
Lamp holder		None
Special features		C300/R300 (auxiliary contacts, UL/CSA, pilot duty)
Technical Data - Mechanical - Terminals		
Terminal capacity (solid/flexible conductor)		0.75 mm ² - 2.5 mm ² (2x) at auxiliary contacts with ferrule 18 - 14 AWG (1x) at auxiliary contacts 18 - 14 AWG (2x) at auxiliary contacts 0.75 mm ² - 2.5 mm ² (1x) at auxiliary contacts with ferrule
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.

10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information		
Model		Integrable

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss13-27-37-13-02 [AKN342018])		
Number of contacts as change-over contact		0
Number of contacts as normally open contact		2
Number of contacts as normally closed contact		0
Number of fault-signal switches		
Rated operation current I_e at AC-15, 230 V	A	4
Type of electric connection		Screw connection
Model		Integrable
Mounting method		Other
Lamp holder		None