

Remote operator, 110-130VAC, for size 2



**Part no. NZM2-XR110-130AC
259830**

General specifications		
Product name		Eaton Moeller series NZM remote operator
Part no.		NZM2-XR110-130AC
EAN		4015082598303
Product Length/Depth		150 millimetre
Product height		105 millimetre
Product width		105 millimetre
Product weight		1.836 kilogram
Compliances		UL/CSA IEC RoHS conform
Certifications		CSA (Class No. 1437-01) UL (File No. E140305) UL489 CSA-C22.2 No. 5-09 CSA certified CSA (File No. 22086) IEC60947 CE marking UL (Category Control Number DIHS) UL listed
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Remote operator
Delivery program		
Type		Accessory Remote operator, can be synchronized
Number of poles		Three-pole/Four-pole
Special features		Cannot be combined with switch-disconnector PN... Do not install M22-CK11(20/02) dual auxiliary contacts in the center auxiliary contact slot in NZM2-XRD
Frame		NZM2
Used with		N(S)2(-4) NZM2(-4)
Technical Data - Electrical		
Voltage type		AC
Voltage rating		110 - 130 V 50/60 Hz
Operating voltage - min		0.85 x Us
Operating voltage - max		1.1 x Us
Rated control supply voltage (Us) at AC, 50 Hz - min		110 V
Rated control supply voltage (Us) at AC, 50 Hz - max		130 V
Rated control supply voltage (Us) at AC, 60 Hz - min		110 V
Rated control supply voltage (Us) at AC, 60 Hz - max		130 V
Rated control supply voltage (Us) at DC - min		0 V
Rated control supply voltage (Us) at DC - max		0 V
Voltage tolerance - min		0.85
Voltage tolerance - max		1.1
Rated operating frequency		50 Hz
Power consumption		350 VA (110 - 130 V AC)
Closing delay		60 ms
Breaking time		300 ms
Number of operations per hour - max		120
Signal duration of remote operator at switch off - min		150 ms
Signal duration of remote operator at switch on - min		30 ms

Technical Data - Mechanical		
Switch drive type		Motor drive
Special features		Cannot be combined with switch-disconnector PN... Do not install M22-CK11(20/02) dual auxiliary contacts in the center auxiliary contact slot in NZM2-XRD
Lifespan, mechanical		20000 operations
Technical Data - Mechanical - Terminals		
Terminal capacity (solid/flexible conductor)		18 - 14 AWG 0.75 mm ² - 2.5 mm ² with ferrule
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Motor operator for power circuit-breaker (EC001030)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Electrical drive for circuit breakers (ecI@ss13-27-37-04-12 [AKF010018])		
Type of switch drive		Motor drive
Rated control supply voltage AC 50 Hz	V	110 - 130
Rated control supply voltage AC 60 Hz	V	110 - 130
Rated control supply voltage DC	V	0 - 0
Voltage type for actuating		AC