

Auxiliary contact, for FAZ, PKNM, 2W, 0.5HP



Part no. FAZ-XAM002
262414
EL Number 1695385
(Norway)

General specifications		
Product name		Eaton Distribution parts
Part no.		FAZ-XAM002
EAN		4015082624149
Product Length/Depth		80 millimetre
Product height		75.5 millimetre
Product width		8.8 millimetre
Product weight		0.045 kilogram
Compliances		RoHS conform
Certifications		CE marking UL (Category Control Number QVNU2, QVNU8) North America (UL listed, certified by UL for use in Canada) CSA-C22.2 No. 235 IEC/EN 60947-2 IEC/EN 60898 CSA (Class No. 3215-30) UL (File No. E177451) UL 1077 IEC 61373 EN45545-2
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		Auxiliary contacts
Additional equipment required		Other
Admissible back-up fuse - max		4 A gL
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Amperage Rating		4 A
Assembly width		0.5
Contact function		2 C/O
Conventional thermal current Ith of auxiliary contacts (1-pole, open)		4 A
Degree of protection		UL/CSA Type: - IP20 (IEC) IP40
Device fitting		Earth leakage circuit breaker and miniature circuit breaker (MCB)
EL number		1695385
Enclosure width		80 mm
Frame		Standard front dimension: 45 mm
Frequency rating		50 Hz / 60 Hz
Functions		Auxiliary switch
Mounting width		8.8 mm (0.5 space units)
Number of contacts (change-over contacts)		2
Number of contacts (normally closed contacts)		0
Number of contacts (normally open contacts)		0
Number of poles at main contact unit - max		2
Number of switches (fault signal)		0
Rated conditional short-circuit current (Iq) with 6 a back-up fuse		1 kA
Rated impulse withstand voltage (Uimp)		2.5 kV

Rated insulation voltage (Ui)			250 V AC
Rated operational current			3 A (250 V AC-12) 0.5 A (110 V DC-13) 2 A (250 V AC-15)
Rated operational voltage (Ue) - max			250 V
Rated switch current			3 A
Suitable for current of main contact unit - max			0 A
Terminal capacity (cable)			0.5 mm ² - 2.5 mm ²
Terminal capacity (solid wire)			0.5 mm ² - 2.5 mm ²
Terminal protection			Protection against electric shock to IEC 536
Terminal type			Lift terminals
Type			Accessory Accessory for miniature circuit breaker
Used with			Accessory for miniature circuit breaker Accessory
Voltage rating			250 V AC
Voltage rating per contact - min			5 V DC
Voltage type			AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])			
Device fitting			Earth leakage circuit breaker and miniature circuit breaker (MCB)
Function			Auxiliary switch
Width in number of modular spacings			0.5
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			2
Number of fault-signal switches			0
Rated switch current		A	3
Rated voltage		V	250
Voltage type			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			2
Suitable for max. current main contact unit		A	0