

Fuse disconnectors, 2 p, 10 x 38



Part no. **Z-SHL/2**
263885

| General specifications | | |
|--|--|--------------------------------------|
| Product name | | Eaton Distribution parts |
| Part no. | | Z-SHL/2 |
| EAN | | 4015082638856 |
| Product Length/Depth | | 80 millimetre |
| Product height | | 74 millimetre |
| Product width | | 35 millimetre |
| Product weight | | 0.164 kilogram |
| Compliances | | RoHS conform |
| Product Tradename | | None |
| Product Type | | Distribution parts |
| Product Sub Type | | None |
| Public Consumption | | Yes |
| Product Family Description | | ES-PMCC-PDC-Eaton Distribution parts |
| Globally Marketable | | Yes |
| Product Specification Details | | |
| Actuator position | | Front side |
| Actuator type | | Other |
| Cable entry type | | Other |
| Conditioned rated short-circuit current Iq | | 10 kA |
| Degree of protection (front side) | | IP20 |
| Electrical connection type of main circuit | | Screw connection |
| Number of poles | | Two-pole |
| Power rating at AC-23, 400 V | | 0 kW |
| Rated conditional short-circuit current (Iq) | | 10 kA |
| Rated operating voltage (Ue) at AC - max | | 400 V |
| Rated operation power at AC-23, 400 V | | 0 kW |
| Rated short-time withstand current (Icw) | | 0 kA |
| Rated uninterrupted current (Iu) | | 32 A |
| Suitable for fuses | | Shape C1-C3 |

Technical data ETIM 9.0

| | | |
|--|----|------------------|
| Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecl@ss13-27-37-14-01 [AKF058018]) | | |
| Version as main switch | | No |
| Version as safety switch | | No |
| Max. rated operation voltage Ue AC | V | 400 |
| Rated permanent current Iu | A | 32 |
| Rated operation power at AC-23, 400 V | kW | 0 |
| Conditioned rated short-circuit current Iq | kA | 10 |
| Rated short-time withstand current Icw | kA | 0 |
| Suitable for fuses | | Shape C1-C3 |
| Number of poles | | 2 |
| With error protection | | No |
| Type of electrical connection of main circuit | | Screw connection |
| Cable entry | | Other |
| Equipped with connectors | | No |
| Suitable for floor mounting | | No |

| | | | |
|--|--|--|------------|
| Suitable for front mounting | | | No |
| Suitable for busbar mounting | | | No |
| Type of control element | | | Other |
| Position control element | | | Front side |
| Motor drive optional | | | No |
| Motor drive integrated | | | No |
| Version as emergency stop installation | | | No |
| Degree of protection (IP), front side | | | IP20 |