



Fuse disconnectors, 1p, 20A, 8, 5 x 31, 5

Part no. Z-SIL/20/1
 Catalog No. 263901

Similar to illustration

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecl@ss10.0.1-27-37-14-01 [AKF058013])		
Version as main switch		No
Version as safety switch		No
Max. rated operation voltage Ue AC	V	230
Rated permanent current Iu	A	32
Rated operation power at AC-23, 400 V	kW	0
Conditioned rated short-circuit current Iq	kA	10
Rated short-time withstand current Icw	kA	0
Suitable for fuses		Shape C1-C3
Number of poles		1
With error protection		No
Type of electrical connection of main circuit		Screw connection
Cable entry		Other
Equipped with connectors		No
Suitable for ground mounting		No
Suitable for front mounting 4-hole		No
Suitable for busbar mounting		No
Type of control element		Other
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP20