

Phase busbar, 3-phases, 16qmm, pin, 1m

Part no. **Z-SV-16/3P-3TE**
264925

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-SV-16/3P-3TE
EAN		4015082649258
Product Length/Depth		29.5 millimetre
Product height		16.2 millimetre
Product width		1020 millimetre
Product weight		0.652 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Color		Other
Cross section		16 mm ²
Electric connection type		Pin
Features		Insulated Can be cut to size
Number of modular spacings		3
Number of phases		3
Number of poles		Three-pole
Pitch dimensions		17.95 mm
Rated conditional short-circuit current (I _q)		25 kA
Rated operational voltage (U _e) - max		415 V
Rated short-time withstand current (I _{cw})		0 kA
Rated surge voltage		0 kV
Rated uninterrupted current (I _u)		63 A
Suitable for		19 devices
Suitable for number of devices		0

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016])		
Number of phases		3
Number of poles		3
Suitable for number of devices		0
Module width	mm	17.95
Cross section	mm ²	16
Length	mm	29.5
Can be cut to size		Yes
Width in number of modular spacings		3
Rated permanent current I _u	A	63
Type of electric connection		Pin
Insulated		Yes
Rated surge voltage	kV	0

Conditioned rated short-circuit current Iq	kA	25
Max. rated operation voltage Ue	V	415
Rated short-time withstand current Icw	kA	0
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Other