

Additional handle, for size 3/4



**Part no.** **NZM3/4-XDZ**  
**266622**

<b>General specifications</b>		
Product name		Eaton Moeller series NZM operating element accessory
Part no.		NZM3/4-XDZ
EAN		4015082666224
Product Length/Depth		200 millimetre
Product height		70 millimetre
Product width		55 millimetre
Product weight		0.271 kilogram
Compliances		IEC UL/CSA RoHS conform
Certifications		UL (File No. E140305) UL (Category Control Number DIHS) UL listed UL489 IEC60947 CSA (Class No. 1437-01) CSA (File No. 22086) CE marking CSA certified CSA-C22.2 No. 5-09
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Operating element accessory
<b>Delivery program</b>		
Type		Accessory Additional handle
Special features		Enables switching when control panel door is open
Frame		NZM3/4
Suitable for		Power circuit breaker Switch disconnecter
Used with		NZM3(-4), PN3(-4), N(S)3(-4) NZM4(-4), N(S)4(-4)
<b>Technical Data - Mechanical</b>		
Color		Gray
Degree of protection / NEMA enclosure type		Other
Special features		Enables switching when control panel door is open
<b>Design verification as per IEC/EN 61439</b>		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.

10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])			
With restart blockage			No
With key lock			No
Padlock locking			No
Colour			Grey
Suitable for emergency stop			No
With extension shaft			No
Suitable for power circuit breaker			Yes
Suitable for switch disconnecter			Yes
Degree of protection (NEMA)			Other