

Main switch assembly kit, handle black, size 3



Part no. NZM3-XHB
266628
EL Number 4315577
(Norway)

General specifications		
Product name		Eaton Moeller series NZM operating element
Part no.		NZM3-XHB
EAN		4015082666286
Product Length/Depth		230 millimetre
Product height		110 millimetre
Product width		140 millimetre
Product weight		1.574 kilogram
Compliances		IEC UL/CSA RoHS conform
Certifications		CSA (File No. 22086) CSA (Class No. 1437-01) CSA certified CE marking UL (Category Control Number DIHS) UL489 UL listed UL (File No. E140305) IEC60947 CSA-C22.2 No. 5-09
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Operating element
Delivery program		
Type		Accessory Main switch assembly kit
Features		Lockable With black door coupling rotary handle
Special features		External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as a main switch
Frame		NZM3
Fitted with:		NZM...-XV4 extension shaft Door coupling rotary handle with rotary drive External warning plate/markings plate in German/English Black and yellow lightning symbol Padlock
Suitable for		Power circuit breaker Switch disconnecter
Used with		N(S)3(-4) PN3(-4) NZM3(-4)
Technical Data - Mechanical		
Color		Black
Cover/door type		Door interlock can also be modified in I position After the door interlock is activated, must not be opened while on ON or TRIP. Must only be opened on OFF Door interlock can only be switched ON when the door is closed Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door interlock on OFF with max. 3 padlocks Door interlock not defeated in the locked OFF position.
Degree of protection / NEMA enclosure type		IP66 4X. 12
Locking facility		With door interlock Lockable on the 0 position on the handle using up to 3 padlocks Can also be modified in I position
Special features		External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as a main switch
Design verification as per IEC/EN 61439		

10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])		
With restart blockage		No
With key lock		No
Padlock locking		Yes
Colour		Black
Suitable for emergency stop		No
With extension shaft		No
Suitable for power circuit breaker		Yes
Suitable for switch disconnecter		Yes
Degree of protection (NEMA)		4X, 12