

Contactors, 3 pole, 380 V 400 V 7.5 kW, 1 NC, 400 V 50 Hz, 440 V 60 Hz, AC operation, Screw terminals



**Part no. DILM17-01(400V50HZ,440V60HZ)
277038**

| | |
|--|---|
| Product name | Eaton Moeller® series DILM contactor |
| Part no. | DILM17-01(400V50HZ,440V60HZ) |
| EAN | 4015082770389 |
| Product Length/Depth | 97 millimetre |
| Product height | 85 millimetre |
| Product width | 45 millimetre |
| Product weight | 0.428 kilogram |
| Certifications | IEC/EN 60947 CSA VDE 0660 UL |
| Product Tradename | DILM |
| Product Type | Contactors |
| Product Sub Type | None |
| Catalog Notes | Contacts according to EN 50012 |
| Fitted with: | Mirror contact |
| Application | Contactors for Motors |
| Degree of protection | IP00 |
| Frame size | FS2 |
| Lifespan, mechanical | 10,000,000 Operations (AC operated) |
| Operating frequency | 5000 mechanical Operations/h (AC operated) |
| Overvoltage category | III |
| Pollution degree | 3 |
| Product category | Contactors |
| Protection | Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) |
| Rated impulse withstand voltage (Uimp) | 8000 V AC |
| Resistance per pole | 2.7 |
| Suitable for | Also motors with efficiency class IE3 |
| Utilization category | AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-3: Normal AC induction motors: starting, switch off during running AC-4: Normal AC induction motors: starting, plugging, reversing, inching |
| Voltage type | AC |
| Shock resistance | 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 6.9 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 5.3 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 3.5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms |
| Altitude | Max. 2000 m |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 60 °C |
| Ambient operating temperature (enclosed) - min | 25 °C |
| Ambient operating temperature (enclosed) - max | 40 °C |

| | | |
|---|--|--|
| Ambient storage temperature - min | | 40 °C |
| Ambient storage temperature - max | | 80 °C |
| Climatic proofing | | Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 |
| Emitted interference | | According to EN 60947-1 |
| Interference immunity | | According to EN 60947-1 |
| Terminal capacity (flexible with ferrule) | | 2 x (0.75 - 10) mm ² , Main cables 1 x (0.75 - 16) mm ² , Main cables 2 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 2.5) mm ² , Control circuit cables |
| Terminal capacity (solid) | | 2 x (0.75 - 2.5) mm ² , Control circuit cables 2 x (0.75 - 10) mm ² , Main cables 1 x (0.75 - 4) mm ² , Control circuit cables 1 x (0.75 - 16) mm ² , Main cables |
| Terminal capacity (solid/stranded AWG) | | Single 18 - 6, double 18 - 8, Main cables 18 - 14, Control circuit cables |
| Terminal capacity (stranded) | | 1 x 16 mm ² , Main cables |
| Stripping length (main cable) | | 10 mm |
| Stripping length (control circuit cable) | | 10 mm |
| Screw size | | M3.5, Terminal screw, Control circuit cables M5, Terminal screw, Main cables |
| Screwdriver size | | 0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver |
| Tightening torque | | 3.2 Nm, Screw terminals, Main cables 1.2 Nm, Screw terminals, Control circuit cables |
| Rated breaking capacity at 220/230 V | | 170 A |
| Rated breaking capacity at 380/400 V | | 170 A |
| Rated breaking capacity at 500 V | | 170 A |
| Rated breaking capacity at 660/690 V | | 120 A |
| Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V | | 40 A |
| Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V | | 18 A |
| Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V | | 18 A |
| Rated operational current (Ie) at AC-3, 440 V | | 18 A |
| Rated operational current (Ie) at AC-3, 500 V | | 18 A |
| Rated operational current (Ie) at AC-3, 660 V, 690 V | | 12 A |
| Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V | | 10 A |
| Rated operational current (Ie) at AC-4, 440 V | | 10 A |
| Rated operational current (Ie) at AC-4, 500 V | | 10 A |
| Rated operational current (Ie) at AC-4, 660 V, 690 V | | 8 A |
| Rated operational current (Ie) at DC-1, 60 V | | 35 A |
| Rated operational current (Ie) at DC-1, 110 V | | 35 A |
| Rated operational current (Ie) at DC-1, 220 V | | 35 A |
| Rated insulation voltage (Ui) | | 690 V |
| Rated making capacity up to 690 V (cos phi to IEC/EN 60947) | | 238 A |
| Rated operational power at AC-3, 240 V, 50 Hz | | 5.5 kW |
| Rated operational power at AC-3, 380/400 V, 50 Hz | | 7.5 kW |
| Rated operational power at AC-3, 415 V, 50 Hz | | 10 kW |
| Rated operational power at AC-3, 440 V, 50 Hz | | 10.5 kW |
| Rated operational power at AC-3, 500 V, 50 Hz | | 12 kW |
| Rated operational power at AC-3, 690 V, 50 Hz | | 11 kW |
| Rated operational power at AC-4, 220/230 V, 50 Hz | | 2.5 kW |
| Rated operational power at AC-4, 240 V, 50 Hz | | 3 kW |
| Rated operational power at AC-4, 415 V, 50 Hz | | 5 kW |
| Rated operational power at AC-4, 440 V, 50 Hz | | 5.5 kW |
| Rated operational power at AC-4, 500 V, 50 Hz | | 6 kW |
| Rated operational power at AC-4, 660/690 V, 50 Hz | | 6.5 kW |
| Rated operational voltage (Ue) at AC - max | | 690 V |

| | |
|---|---|
| Short-circuit current rating (basic rating) | 125 A, max. Fuse, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA) 125 A, max. CB, SCCR (UL/CSA) |
| Short-circuit current rating (high fault at 480 V) | 125/70 A, Class J, max. Fuse, SCCR (UL/CSA) 10/65 kA, CB, SCCR (UL/CSA) 50/32 A, max. CB, SCCR (UL/CSA) 10/100 kA, Fuse, SCCR (UL/CSA) |
| Short-circuit current rating (high fault at 600 V) | 10/22 kA, CB, SCCR (UL/CSA) 125/70 A, Class J, max. Fuse, SCCR (UL/CSA) 50/32 A, max. CB, SCCR (UL/CSA) 10/100 kA, Fuse, SCCR (UL/CSA) |
| Short-circuit protection rating (type 1 coordination) at 400 V | 63 A gG/gL |
| Short-circuit protection rating (type 1 coordination) at 690 V | 50 A gG/gL |
| Short-circuit protection rating (type 2 coordination) at 400 V | 35 A gG/gL |
| Short-circuit protection rating (type 2 coordination) at 690 V | 35 A gG/gL |
| Conventional thermal current i_{th} (1-pole, enclosed) | 80 A |
| Conventional thermal current i_{th} (3-pole, enclosed) | 32 A |
| Conventional thermal current i_{th} at 55°C (3-pole, open) | 37 A |
| Conventional thermal current i_{th} at 60°C (3-pole, open) | 35 A |
| Conventional thermal current i_{th} of main contacts (1-pole, open) | 88 A |
| Switching capacity (main contacts, general use) | 40 A, Maximum motor rating (UL/CSA) |
| Switching capacity (auxiliary contacts, general use) | 10 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA) |
| Switching capacity (auxiliary contacts, pilot duty) | P300, DC operated (UL/CSA) A600, AC operated (UL/CSA) |
| Arcing time | 10 ms |
| Drop-out voltage | AC operated: 0.6 - 0.3 x UC, AC operated |
| Duty factor | 100 % |
| Pick-up voltage | 0.8 - 1.1 V AC x U _c |
| Power consumption, pick-up, 50 Hz | 52 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz |
| Power consumption, pick-up, 60 Hz | 67 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz |
| Power consumption, sealing, 50 Hz | 7.1 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz 2.1 W, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz |
| Power consumption, sealing, 60 Hz | 2.1 W, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz 8.7 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz |
| Rated control supply voltage (U _s) at AC, 50 Hz - min | 400 V |
| Rated control supply voltage (U _s) at AC, 50 Hz - max | 400 V |
| Rated control supply voltage (U _s) at AC, 60 Hz - min | 440 V |
| Rated control supply voltage (U _s) at AC, 60 Hz - max | 440 V |
| Rated control supply voltage (U _s) at DC - min | 0 V |
| Rated control supply voltage (U _s) at DC - max | 0 V |
| Switching time (AC operated, make contacts, closing delay) - min | 16 ms |
| Switching time (AC operated, make contacts, closing delay) - max | 22 ms |
| Switching time (AC operated, make contacts, opening delay) - min | 8 ms |
| Switching time (AC operated, make contacts, opening delay) - max | 14 ms |
| Assigned motor power at 115/120 V, 60 Hz, 1-phase | 2 HP |
| Assigned motor power at 200/208 V, 60 Hz, 3-phase | 5 HP |
| Assigned motor power at 230/240 V, 60 Hz, 1-phase | 3 HP |
| Assigned motor power at 230/240 V, 60 Hz, 3-phase | 5 HP |
| Assigned motor power at 460/480 V, 60 Hz, 3-phase | 10 HP |
| Assigned motor power at 575/600 V, 60 Hz, 3-phase | 15 HP |
| Connection | Screw terminals |
| Connection to SmartWire-DT | No |

| | | |
|--|--|--|
| Number of contacts (normally closed contacts) | | 1 |
| Number of auxiliary contacts (normally closed contacts) | | 1 |
| Number of auxiliary contacts (normally open contacts) | | 0 |
| Safe isolation | | 440 V AC, Between the contacts, According to EN 61140 440 V AC, Between coil and contacts, According to EN 61140 |
| Special purpose rating of ballast electrical discharge lamps | | 40 A (480V 60Hz 3phase, 277V 60Hz 1phase) 40 A (600V 60Hz 3phase, 347V 60Hz 1phase) |
| Special purpose rating of refrigeration control (CSA only) | | 180 A, LRA 600 V 60 Hz 3phase; (CSA) 30 A, FLA 600 V 60 Hz 3phase; (CSA) 40 A, FLA 480 V 60 Hz 3phase; (CSA) 240 A, LRA 480 V 60 Hz 3phase; (CSA) |
| Special purpose rating of resistance air heating | | 40 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) 40 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) |
| Special purpose rating of tungsten incandescent lamps | | 40 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 40 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) |
| Equipment heat dissipation, current-dependent Pvid | | 2.1 W |
| Heat dissipation capacity Pdis | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0.7 W |
| Rated operational current for specified heat dissipation (In) | | 18 A |
| Static heat dissipation, non-current-dependent Pvs | | 2.1 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 8.0

| | | |
|---|----|-----------|
| Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015]) | | |
| Rated control supply voltage Us at AC 50HZ | V | 400 - 400 |
| Rated control supply voltage Us at AC 60HZ | V | 440 - 440 |
| Rated control supply voltage Us at DC | V | 0 - 0 |
| Voltage type for actuating | | AC |
| Rated operation current Ie at AC-1, 400 V | A | 40 |
| Rated operation current Ie at AC-3, 400 V | A | 18 |
| Rated operation power at AC-3, 400 V | kW | 7.5 |
| Rated operation current Ie at AC-4, 400 V | A | 10 |

| | | |
|---|----|------------------|
| Rated operation power at AC-4, 400 V | kW | 4.5 |
| Rated operation power NEMA | kW | 7.4 |
| Modular version | | No |
| Number of auxiliary contacts as normally open contact | | 0 |
| Number of auxiliary contacts as normally closed contact | | 1 |
| Type of electrical connection of main circuit | | Screw connection |
| Number of normally closed contacts as main contact | | 0 |
| Number of normally open contacts as main contact | | 3 |