

Door coupling rotary handle, red-yellow, size 3



Part no. NZM3-XTVDVR-0  
279402  
EL Number 4358974  
(Norway)

General specifications		
Product name		Eaton Moeller series NZM operating element
Part no.		NZM3-XTVDVR-0
EAN		4015082794026
Product Length/Depth		100 millimetre
Product height		230 millimetre
Product width		120 millimetre
Product weight		1.275 kilogram
Compliances		IEC UL/CSA RoHS conform
Certifications		CSA-C22.2 No. 5-09 CSA (Class No. 1437-01) UL (Category Control Number DIHS) UL489 CSA (File No. 22086) CE marking UL (File No. E140305) UL listed IEC60947 CSA certified
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Operating element
Delivery program		
Type		Accessory Door coupling rotary handle
Features		Lockable Red-yellow for emergency switching off
Special features		Complete including rotary drive and coupling parts For extremely narrow fittings With special short extension shaft Cannot be combined with NZM...-XDZ additional handle External warning plate/designation label can be clipped on. Door coupling rotary handle for operating the switch through a closed control panel door
Frame		NZM3
Fitted with:		Padlock
Suitable for		Switch disconnecter Emergency stop Power circuit breaker
Used with		NZM3(-4), PN3(-4), N(S)3(-4)
Technical Data - Mechanical		
Color		Red
Cover/door type		Door interlock not defeated in the locked OFF position. Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door interlock can be modified in the unlocked ON position Door can be opened in OFF
Degree of protection / NEMA enclosure type		IP66 4X. 12
Lock number		Double lockable
Locking facility		Lockable on the handle on the switch using up to 3 padlocks With door interlock
Special features		Complete including rotary drive and coupling parts For extremely narrow fittings With special short extension shaft Cannot be combined with NZM...-XDZ additional handle External warning plate/designation label can be clipped on. Door coupling rotary handle for operating the switch through a closed control panel door

Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])		
With restart blockage		No
With key lock		No
Padlock locking		Yes
Colour		Red
Suitable for emergency stop		Yes
With extension shaft		No
Suitable for power circuit breaker		Yes
Suitable for switch disconnector		Yes
Degree of protection (NEMA)		4X, 12