




LED, yellow, BA15d, 230 V

Part no. **SL-LED230-Y**
 Catalog No. **285535**
 Alternate Catalog No. **SL-LED230-Y**

Delivery program

Product range			SL signal towers
Single unit/Complete unit			Stand-alone device
			Socket size BA-15d
Lifespan to EN 60064 at $t_a = +25\text{ °C}$	t_{mean} (AC)	h	100000
Rated operational voltage	U_e	V	110 - 230 V AC 50/60 Hz
Rated operational current	I_e	mA	9 - 17
Colour			
			
Connection to SmartWire-DT			no

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

Technical data ETIM 7.0

Lamps (EG000028) / Single LED (EC001019)			
Electric engineering, automation, process control engineering / Lighting installation, device / Light medium / Single LED (ecl@ss10.0.1-27-11-06-36 [AKE247013])			
Colour			Yellow
Luminous flux		lm	0
Nominal voltage		V	230
Voltage type			AC
Nominal current		mA	17
Power consumption		W	0.12
Diameter		mm	0
Length		mm	0
Beam angle		°	360
Energy efficiency class			Not applicable
Weighted energy consumption in 1,000 hours		kWh	720
Average nominal lifespan		h	100000

Approvals

Product Standards			IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.			E29184
UL Category Control No.			NKCR
CSA File No.			012528

CSA Class No.		3211-03
North America Certification		UL listed, CSA certified