

Surface-mount service distribution board base frame HxW = 460 x 800 mm

Part no. **BP-MF-800/4**

286663

EL Number
(Norway)

2456021

General specifications		
Product name		Eaton xEnergy Basic frame
Part no.		BP-MF-800/4
EAN		4015082866631
Product Length/Depth		50 millimetre
Product height		480 millimetre
Product width		815 millimetre
Product weight		6.4 kilogram
Compliances		RoHS conform
Product Tradename		xEnergy Basic
Product Type		Accessories
Product Sub Type		Frame
Delivery program		
Type		Additional equipment
Color		Stainless steel
Technical Data - Mechanical		
Surface finishing		Galvanized
Mounting method		Surface mounting Wall fastening
Material		Sheet steel Steel
Degree of protection		IP30 IK08 (impact resistance) Other
Number of connector holes		0
Number of covers/doors		0
Number of locks		0
Permissible load of the door(s) according to IEC 62208 - max		0 N
Permissible load of the enclosure according to IEC 62208 - max		0 N
Permissible load of the mounting plate according to IEC 62208 - max		0 N
Grade material		Sheet steel
Installation type		Floor installation possible
Suitable for width		800 mm
Temperature-rise verification as per IEC 60890		
Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890		0 W
Additional information		
Features		Connectable EMC-version
Functions		Additional equipment
RAL-number		0
Suitable for		Metrical mounting

Technical data ETIM 9.0

Cabinet enclosures (EG000011) / Enclosure/cabinet (empty) (EC000261)		
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet, Empty enclosures (ecl@ss13-27-18-01-01 [AGZ056021])		
Width	mm	815
Height	mm	480
Depth	mm	50

Material			Steel
Material quality			Other
Surface finishing			Galvanized
Colour			Stainless steel
RAL-number			0
Freestanding			No
Floor standing wall model			No
Suitable for wall mounting			Yes
Corner model			No
Intermediate mounting			No
Couplable			Yes
With mounting plate			No
Mounting plate depth-adjustable			No
Suitable for wall built-in			No
Pole fastening			No
With door			No
Number of doors			0
With glazed door			No
With ventilation door			No
With rear door			No
Number of locks			0
With cover			No
Transparent cover			No
Suitable for metrical mounting			Yes
Suitable for outdoor set-up			No
Pitched roof			No
Number of connector holes			0
Pre-stamping			No
EMC-version			Yes
Impact strength			IK08
Degree of protection (IP)			IP30
Degree of protection (NEMA)			Other
Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890		W	0
Max. permissible load of the enclosure according to IEC 62208		N	0
Max. permissible load of the door(s) according to IEC 62208		N	0
Max. permissible load of the mounting plate according to IEC 62208		N	0