



**Eaton 9PX 11000i RT6U HotSwap Netpack**



**Part no.  
Catalog No.**

**Eaton 9PX 11000i RT6U HotSwap Netpack  
9PX11KIRTNBP**

## Delivery program

|               |  |     |
|---------------|--|-----|
| Product range |  | UPS |
|---------------|--|-----|

## Technical data ETIM 7.0

|  |     |                           |
|--|-----|---------------------------|
| Data and telecommunication (EG000037) / UPS (EC000382)   |     |                           |
| Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) (ecl@ss10.0.1-27-04-06-90 [BAB258012]) |     |                           |
| Input voltage  | V   | 100 - 276                 |
| Primary frequency  | Hz  | 40 - 70                   |
| Number of phases primary   |     | 1                         |
| Output voltage   | V   | 200 - 250                 |
| Secondary frequency  | Hz  | 50 - 60                   |
| Output effective power   | W   | 10000                     |
| Output apparent power  | VA  | 11000                     |
| Type of interface  |     | Other                     |
| Number of phases secondary   |     | 1                         |
| SNMP   |     | Yes                       |
| Voltage type   |     | AC                        |
| Height   | mm  | 440                       |
| Width  | mm  | 260                       |
| Depth  | mm  | 700                       |
| Transition time for full load  | min | 3                         |
| Weight   | kg  | 86                        |
| Network-management   |     | Yes                       |
| USV- technology  |     | Online                    |
| Construction type  |     | 482.6 mm (19 inch) device |
| Max. voltage distortion output (linear load)   | %   | 2                         |
| Output power factor  |     | 0.9                       |
| Overall efficiency   | %   | 95                        |
| Efficiency in eco-mode   | %   | 98                        |
| Potential free switch contact  |     | Yes                       |
| Auto shut down function  |     | Yes                       |
| Input connection   |     | Fixed connection          |
| Number of output connections C13   |     | 0                         |
| Number of output connections C19   |     | 4                         |
| Number of output connections with protective contact (SCHUKO)  |     | 0                         |
| Number of output connections fixed connection  |     | 1                         |