

**Padlocking feature**



**Part no. SVC-T3  
050975**

<b>General specifications</b>	
Product name	Eaton Moeller® series SVC Accessory Padlocking feature
Part no.	SVC-T3
EAN	4015080509752
Product Length/Depth	45 millimetre
Product height	73 millimetre
Product width	49 millimetre
Product weight	0.08 kilogram
Compliances	CE
Product Tradename	SVC
Product Type	Accessory
Product Sub Type	Padlocking feature
Catalog Notes	The positions that can be interlocked can be programmed by the user
<b>Features &amp; Functions</b>	
Fitted with:	Label area
Functions	Padlocking
Locking facility	Lockable with a maximum of 3 padlocks
Material	Polycarbonate
<b>General information</b>	
Degree of protection	IP65, front
Type	Locking arrangements
<b>Climatic environmental conditions</b>	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	50 °C
<b>Design verification</b>	
Equipment heat dissipation, current-dependent P <sub>vid</sub>	0 W
Heat dissipation capacity P <sub>diss</sub>	0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>	0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )	0 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	Not applicable.

10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Padlock barrier for switch (EC002051)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Padlock barrier for switch (ecl@ss13-27-37-13-07 [ACN994016])			
Max. number of padlocks			3
Suitable for shackle diameter		mm	2 - 4
With label area			Yes
Material			Polycarbonate (PC)