Flange plate, IP66, insulating material, 2xD=7-70mm



Part no. F3A-KTD 083674 EL Number 2473242

(Norway)

General specifications	
Product name	Eaton xEffect Accessories cable flange plastic
Part no.	F3A-KTD
EAN	4015080836742
Product Length/Depth	20 millimetre
Product height	140 millimetre
Product width	230 millimetre
Product weight	0.203 kilogram
Compliances	RoHS conform
Product Tradename	xEffect Accessories
Product Type	Cable
Product Sub Type	Flange plastic
Delivery program	
Туре	Accessory CSAccessory exterior fitting
Model	Other
Accessory/spare part type	Flanges
Technical Data - Mechanical	
Surface finishing	RAL 7035, light gray
Surface protection	Untreated
Material	Insulating material Plastic
Degree of protection	Other
Number of connector holes	0
Cable entry type	2 cables up to 70 mm \varnothing
Thickness	4 in
Thread type	None
Suitable for cable diameter - min	7 in
Additional information	
Features	Pre-stamping
Special features	With cable grommets
Used with	Accessory exterior fitting Accessory CS

Technical data ETIM 8.0

Distribution boards (EG000023) / Gland plate for enclosure/cabinet (EC000211)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Gland plate for small distribution boards/switchgear cabinets (ecl@ss10.0.1-27-14-24-21 [ADI315007])

Type Width Width Midth M	boards/switchgear cabinets (eci@ss10.0.1-2/-14-24-21 [ADI31900/])				
Widthmm230Heightmm140Depthmm20MaterialPlasticSurface protectionUntreatedDegree of protection (NEMA)UntreatedPre-stampingYesNumber of connector holesUnitreatedThread typeNone	Model		Other		
Height mm 140 Depth mm 20 Material Plastic Surface protection Degree of protection (NEMA) Pre-stamping Number of connector holes Thread type mm 20 Untreated Plastic Untreated Other Other Yes None	Туре		Straight		
Depth Material Surface protection Degree of protection (NEMA) Pre-stamping Number of connector holes Thread type mm 20 Untreated Plastic Untreated Ves Ves None	Width	mm	230		
Material Plastic Surface protection Untreated Degree of protection (NEMA) Other Pre-stamping Yes Number of connector holes 0 Thread type None	Height	mm	140		
Surface protection Degree of protection (NEMA) Pre-stamping Number of connector holes Thread type Untreated Other Yes O None	Depth	mm	20		
Degree of protection (NEMA) Pre-stamping Number of connector holes Thread type Other Yes O None	Material		Plastic		
Pre-stamping Yes Number of connector holes 0 Thread type None	Surface protection		Untreated		
Number of connector holes 0 Thread type None	Degree of protection (NEMA)		Other		
Thread type None	Pre-stamping		Yes		
	Number of connector holes		0		
Suitable for nominal thread metric/PG 7 - 70	Thread type		None		
	Suitable for nominal thread metric/PG		7 - 70		