

Indicator light, flush, red, +filament lamp, 24 V

Part no. **Q25LF-RT/WB**
089104

General specifications	
Product name	Eaton Moeller® series RMQ16 Indicator light
Part no.	Q25LF-RT/WB
EAN	4015080891048
Product Length/Depth	59 millimetre
Product height	25 millimetre
Product width	25 millimetre
Product weight	0.011 kilogram
Certifications	CSA Class No.: 3211-03 CE UL CSA CSA File No.: 46552 IEC/EN 60947 UL File No.: E29184 UL 508 CSA-C22.2 No. 14-05 IEC/EN 60947-5 UL Category Control No.: NKCR
Product Tradename	RMQ16
Product Type	Indicator light
Product Sub Type	None
Catalog Notes	Use of insulated ferrule ISH 2,8 > 24 V AC/DC recommended Use of insulated ferrule ISH 2,8 > 50 V AC or 120 V DC is mandatory, even on unused blade terminals
Features & Functions	
Bezel color	Black
Bezel material	Plastic
Design	Flush
Fitted with:	Front ring
Lens color	Red
General information	
Degree of protection	NEMA 1
Degree of protection (front side)	IP65
Opening diameter	16 mm
Overvoltage category	III
Pollution degree	3
Product category	RMQ16
Size	Front dimensions: 25 × 25 mm
Rated impulse withstand voltage (Uimp)	800 V AC
Terminal capacity	0.5 - 1.0 mm ²
Terminal size	2.8 x 0.8 mm to DIN 46244, Blade terminal 2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors
Type	Indicator lights
Ambient conditions, mechanical	
Mounting position	As required
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	60 °C
Ambient operating temperature (enclosed) - min	25 °C
Ambient operating temperature (enclosed) - max	40 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30

		Damp heat, constant, to IEC 60068-2-78
Electrical rating		
Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) at AC - max		24 V
Communication		
Connection to SmartWire-DT		No
Design verification		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		1 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for indicator light (EC000223)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for warning lights (ecl@ss13-27-37-12-11 [AKF029019])		
Suitable for number of built-in signal lights		1
Colour lens		Red
Construction type lens		Square
Hole diameter	mm	16
Width opening	mm	0
Height opening	mm	16
With front ring		Yes
Material front ring		Plastic
Colour front ring		Black
Type of lens		Flat
Degree of protection (IP), front side		IP65
Degree of protection (NEMA)		1