

Door coupling rotary handle, black, lockable on the handle+switch, size
4

Part no. **NZM4-XTVDV-NA**
100686

General specifications	
Product name	Eaton Moeller series NZM operating element NA
Part no.	NZM4-XTVDV-NA
EAN	4015081005864
Product Length/Depth	230 millimetre
Product height	130 millimetre
Product width	230 millimetre
Product weight	1.78 kilogram
Compliances	UL/CSA IEC RoHS conform
Certifications	IEC60947 CSA certified UL (File No. E140305) CSA (Class No. 1437-01) CSA-C22.2 No. 5-09 UL489 CE marking UL listed CSA (File No. 22086) UL (Category Control Number DIHS)
Product Tradename	NZM
Product Type	Accessories
Product Sub Type	Operating element NA
Delivery program	
Type	Accessory Door coupling rotary handle
Features	Standard: black / gray Lockable
Special features	Complete including rotary drive and coupling parts Extension shaft additionally required. Cannot be combined with mechanical interlock External warning plate/ designation label can be clipped on. Door coupling rotary handle for operating the switch through a closed control panel door
Frame	NZM4
Fitted with:	Padlock Extension shaft
Suitable for	Switch disconnecter Power circuit breaker
Used with	NZM4, N(S)4
Technical Data - Mechanical	
Color	Black
Cover/door type	Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door opens only with active rotation beyond the 0 position Door interlock not defeated in the locked OFF position.
Degree of protection / NEMA enclosure type	IP66 4X. 12
Lock number	Double lockable
Locking facility	With door interlock Lockable on the handle on the switch using up to 3 padlocks
Special features	Complete including rotary drive and coupling parts Extension shaft additionally required. Cannot be combined with mechanical interlock External warning plate/ designation label can be clipped on. Door coupling rotary handle for operating the switch through a closed control panel door
Design verification as per IEC/EN 61439	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])			
With restart blockage			No
With key lock			No
Padlock locking			Yes
Colour			Black
Suitable for emergency stop			No
With extension shaft			Yes
Suitable for power circuit breaker			Yes
Suitable for switch disconnecter			Yes
Degree of protection (NEMA)			4X, 12