

Terminal cover, top 3p, knockout



**Part no.**                    **+NZM2-XKSFAO**  
**108269**

| <b>General specifications</b>  |  |  |
|--|--|--|
| Product name   |  | Eaton Moeller series NZM connection type   |
| Part no.   |  | +NZM2-XKSFAO   |
| EAN  |  | 4015081079056  |
| Product Length/Depth   |  | 72 millimetre  |
| Product height   |  | 25 millimetre  |
| Product width  |  | 102 millimetre   |
| Product weight   |  | 0.036 kilogram   |
| Compliances  |  | IEC<br>RoHS conform  |
| Product Tradename  |  | NZM  |
| Product Type   |  | Accessories  |
| Product Sub Type   |  | Connection type  |
| <b>Delivery program</b>  |  |  |
| Type   |  | Accessory Terminal Terminal cover  |
| Number of poles  |  | Three-pole   |
| Frame  |  | NZM2   |
| Used with  |  | DS7-34...SX200...<br>NZM2, PN2, N(S)2<br>DS7-34...SX160...<br>DS6-340-75K...110K<br>DS7-34...SX135...                            |
| <b>Design verification as per IEC/EN 61439</b>                                   |  |  |
| 10.2.2 Corrosion resistance  |  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components                           |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>Additional information</b>  |  |  |
| Phase separator type   |  | Other  |