

**Variable frequency drive, 600 V AC, 3-phase, 37 kW, IP21, Radio interference suppression filter, OLED display, FR7**



**Part no. SPX040A1-5A4N1**

**125321**

**EL Number**

**4100136**

**(Norway)**

| <b>General specifications</b>                        |  |  |
|--|--|--|
| Product name   |  | Eaton SPX variable frequency drive   |
| Part no.   |  | SPX040A1-5A4N1   |
| EAN  |  | 4015081229277  |
| Product Length/Depth                                 |  | 640 millimetre   |
| Product height                                       |  | 257 millimetre   |
| Product width  |  | 237 millimetre   |
| Product weight                                       |  | 35 kilogram  |
| Certifications                                       |  | Certified by UL for use in Canada<br>IEC/EN61800-3<br>CSA-C22.2 No. 14<br>UL report applies to both US and Canada<br>CSA Class No.: 3211-06<br>Safety: EN 61800-5-1: 2003<br>RCM<br>IEC/EN 61800-3<br>IEC/EN61800-5<br>CUL<br>RoHS, ISO 9001<br>UL<br>UL 508C<br>Specification for general requirements: IEC/EN 61800-2<br>UL File No.: E134360<br>DNV<br>UL Category Control No.: NMMS, NMMS2, NMMS7, NMMS8<br>CE |
| Product Tradename                                    |  | SPX  |
| Product Type   |  | Variable frequency drive   |
| Product Sub Type                                     |  | None   |
| Catalog Notes  |  | Assigned motor rating: For AC motors with internal and external ventilation with 50 Hz / 60 Hz<br>Assigned motor rating: Overload cycle for 60 s every 600 s   |
| <b>General information</b>                           |  |  |
| Degree of protection                                 |  | IP21<br>NEMA Other   |
| Electromagnetic compatibility                        |  | 1st and 2nd environments (according to EN 61800-3)   |
| Fitted with:   |  | OLED display<br>DC link choke<br>Internal DC link<br>IGBT inverter<br>Radio interference suppression filter  |
| Frame size   |  | FR7  |
| Mounting position                                    |  | Vertical   |
| Product Category                                     |  | Variable frequency drives  |
| Protection   |  | Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)  |
| Radio interference class                             |  | C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.  |
| Suitable for   |  | Branch circuits, (UL/CSA)  |
| <b>Climatic environmental conditions</b>             |  |  |
| Altitude   |  | Max. 1000 m<br>Above 1000 m with 1 % performance reduction per 100 m<br>Max. 3000 m  |
| Ambient operating temperature - min                  |  | -10 °C   |
| Ambient operating temperature - max                  |  | 50 °C  |
| Ambient operating temperature at 150% overload - min |  | -10 °C   |
| Ambient operating temperature at 150% overload - max |  | 50 °C  |
| Ambient storage temperature - min                    |  | -40 °C   |

|   |  |  |
|---|--|--|
| Ambient storage temperature - max                             |  | 70 °C  |
| Climatic proofing   |  | < 95 % relative humidity, no condensation, no corrosion, no dripping water   |
| <b>Main circuit</b>   |  |  |
| Mains voltage - min   |  | 525 V  |
| Mains voltage - max   |  | 690 V  |
| Operating mode  |  | Sensorless vector control (SLV)<br>Optional: Vector control with feedback (CLV)<br>U/f control   |
| Output frequency - min  |  | 0 Hz   |
| Output frequency - max  |  | 320 Hz   |
| Output voltage (U2)   |  | 600 V AC, 3-phase<br>690 V AC, 3-phase   |
| Rated control supply voltage                                  |  | 10 V DC (Us, max. 10 mA)   |
| Rated frequency - min   |  | 45 Hz  |
| Rated frequency - max   |  | 66 Hz  |
| Rated operational current (Ie) at 110% overload               |  | 52 A   |
| Rated operational current (Ie) at 150% overload               |  | 41 A   |
| Rated operational power at 690 V, 50 Hz                       |  | 37 kW  |
| Rated operational power at 690 V, 50 Hz, 110% overload        |  | 45 kW  |
| Rated operational voltage                                     |  | 690 V AC, 3-phase<br>600 V AC, 3-phase   |
| Resolution  |  | 0.01 Hz (Frequency resolution, setpoint value)   |
| Supply frequency  |  | 50/60 Hz   |
| Switching frequency   |  | 1.5 kHz, 1 - 6 kHz adjustable, fPWM, Power section, Main circuit   |
| System configuration type                                     |  | AC supply systems with earthed center point  |
| Voltage rating - max  |  | 690 V AC   |
| <b>Motor rating</b>   |  |  |
| Assigned motor current IM at 690 V, 50 Hz, 110% overload      |  | 47 A   |
| Assigned motor current IM at 690 V, 50 Hz, 150% overload      |  | 39 A   |
| Assigned motor current IM at 690 V, 60 Hz, 110% overload      |  | 45 A   |
| Assigned motor current IM at 690 V, 60 Hz, 150% overload      |  | 36 A   |
| Assigned motor power at 690 V, 60 Hz                          |  | 40 HP  |
| Assigned motor power at 690 V, 60 Hz, 110% overload           |  | 50 HP  |
| <b>Control circuit</b>  |  |  |
| Number of inputs (analog)                                     |  | 2 (parameterizable, 0 - 10 V DC, 0/4 - 20 mA)  |
| Number of inputs (digital)                                    |  | 6 (parameterizable, max. 30 V DC)  |
| Number of outputs (analog)                                    |  | 1  |
| Number of outputs (digital)                                   |  | 1 (parameterizable, 48 V DC/50 mA)   |
| Number of relay outputs                                       |  | 2 (parameterizable, N/O, 8 A (24 V DC) / 8 A (250 V AC) / 0,4 A (125 V DC))  |
| Rated control voltage (Uc)                                    |  | 24 V DC (external, max. 250 mA)  |
| <b>Communication</b>  |  |  |
| Communication interface                                       |  | PROFIBUS-DP<br>DeviceNet, optional<br>BACnet/IP, optional<br>Modbus-TCP, optional<br>LonWorks, optional<br>CANopen®, optional<br>BACnet MS/TP, optional<br>EtherCAT, optional<br>Ethernet IP, optional<br>Modbus-RTU, optional<br>PROFINET, optional |
| Connection to SmartWire-DT                                    |  | No   |
| <b>Design verification</b>                                    |  |  |
| Equipment heat dissipation, current-dependent Pvid            |  | 925 W  |
| Heat dissipation capacity Pdiss                               |  | 0 W  |
| Heat dissipation per pole, current-dependent Pvid             |  | 0 W  |
| Rated operational current for specified heat dissipation (In) |  | 41 A   |
| Static heat dissipation, non-current-dependent Pvs            |  | 0 W  |
| Heat dissipation details                                      |  | Operation (with 150 % overload)  |

|  |  |  |  |
|--|--|--|--|
| 10.2.2 Corrosion resistance  |  |  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         |  |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  |  | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 |  |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  |  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  |  | Meets the product standard's requirements.   |
| 10.6 Incorporation of switching devices and components                           |  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                |  |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   |  |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         |  |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |