## Terminal jumper, with cover 4p/2p

Part no. NZM3-4-XKV2P

131731 4356083

**EL Number** (Norway)



| General specifications   |  |
|--|--|
| Product name   | Eaton Moeller series NZM link kit  |
| Part no.   | NZM3-4-XKV2P   |
| EAN  | 4015081287000  |
| Product Length/Depth   | 190 millimetre   |
| Product height   | 154 millimetre   |
| Product width  | 112 millimetre   |
| Product weight   | 1.478 kilogram   |
| Compliances  | IEC  |
| Compilation  | RoHS conform   |
| Product Tradename  | NZM  |
| Product Type   | Accessories  |
| Product Sub Type   | Link kit   |
| Delivery program   |  |
| Туре   | Accessory DC link kit Terminal   |
| Number of poles  | Two-pole   |
| Amperage Rating  | 517 A (40 °C), 435 A (65 °C)   |
| Special features   | Jumper kit with cover IP2X   |
| Frame  | NZM3   |
| Suitable for   | Four-pole  |
| Used with  | N3-4S1(-S15)-DC  |
| Technical Data - Mechanical  |  |
| Special features   | Jumper kit with cover IP2X   |
| Design verification as per IEC/EN 61439  |  |
| 10.2.2 Corrosion resistance  | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures                         | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat       | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                 | Meets the product standard's requirements.   |
| 10.2.5 Lifting   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components                           | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections                                | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength   | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material                         | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

| Additional information |       |  |
|------------------------|-------|--|
| Model                  | Other |  |

## **Technical data ETIM 9.0**

| Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)  |       |  |
|---|-------|--|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss13-27-37-04-24 [ACN957016]) |       |  |
| Suitable for number of poles  | 4     |  |
| Model   | Other |  |