

Busbar adapter, 4p, for NZM2, 250A, UL508



**Part no.** NZM2-4-XAD250  
**138388**  
**EL Number** 1718009  
**(Norway)**

General specifications		
Product name		Eaton xEffect SASY 60i MCCB adapter
Part no.		NZM2-4-XAD250
EAN		4015081351688
Product Length/Depth		35 millimetre
Product height		270 millimetre
Product width		140 millimetre
Product weight		1.8 kilogram
Compliances		RoHS conform
Product Tradename		xEffect SASY 60i
Product Type		Busbar system component
Product Sub Type		MCCB adapter
Delivery program		
Type		60 mm system Busbar adapters for NZM
Nominal current		250 A
Number of poles		Four-pole
Technical Data - Electrical		
Voltage rating at AC		690 V AC
Rated operation current (Ie)		250 A
Electric connection type		Other
Creepage resistance		CTI 200
Technical Data - Mechanical		
Rail width		30 mm
Busbar distance		60 mm
Busbar thickness - min		5 mm
Busbar thickness - max		10 mm
Busbar adapter width		140 mm
Adapter width		140 mm
Design verification as per IEC/EN 61439 - technical data		
Temperature resistance		Up to 120 °C
Additional information		
Features		Self-extinguishing acc. UL 94
Functions		Busbar adapters for NZM Component adapter for circuit breakers and switch-disconnector
Suitable for		Surface mounting on flat copper busbars 12 – 30 x 5 – 10, double T and triple T profile
Used with		NZM2(-4), PN2(-4), N2(-4)

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ecl@ss13-27-37-03-04 [ACN951016])		
Mounting rail armament		None
Type of electric connection		Other
Rated current In	A	250
Min. busbar thickness	mm	5
Max. busbar thickness	mm	10
Width of the adapter	mm	140

Rail width	mm	30
Busbar distance	mm	60