Base module;quick-mounting;100 mm aluminum tube



Part no. SL4-FMS-100

171308

EL Number 4137544

(Norway)

General specifications	
Product name	Eaton Moeller® series SL4 Base module
Part no.	SL4-FMS-100
EAN	4015081678495
Product Length/Depth	81 millimetre
Product height	171 millimetre
Product width	81 millimetre
Product weight	0.172 kilogram
Certifications	CSA-C22.2 No. 94-91
Continuations	Certified by UL for use in Canada CSA Class No.: NKCR7 IEC/EN 60947-5-1 UL File No.: E29184 UL CE IEC/EN 60529 UL report applies to both US and Canada UL Category Control No.: NKCR UL 508 CSA-C22.2 No. 14-10
Product Tradename	SL4
Product Type	Base module
Product Sub Type	None
Features & Functions	
Color	Other
Fitted with:	Cover Base adapter for slipping onto place (rapid mounting and wiring system)
Number of modules	Max. 5 (with standard base) Max. 10 (with base for mounting on both sides) Max. 5
General information	
Connection to SmartWire-DT	No
Degree of protection	IP66 NEMA 4X NEMA 13 NEMA 4
Mounting Method	Floor Bracket Horizontal
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Tube length	100 mm
Туре	Base module
Climatic environmental conditions	
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	0° C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Terminal capacities	
Terminal capacity (AWG)	24 - 16
Terminal capacity (flexible with ferrule and plastic collar)	0.25 - 0.75 mm ²

Terminal capacity (solid/flexible)	0.2 - 1.5 mm ²
Terminal capacity (solid/flexible with ferrule)	0.25 - 1.5 mm²
Electrical rating	
Rated insulation voltage (Ui)	250 V
Rated operational voltage	24 V AC/DC ± 10 % 230/240 V AC ± 10 % 110/120 V AC ± 10 %

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Connection module for signal tower (EC001152)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, connection module (ecl@ss13-27-37-12-32 [AKF050019])

onnection type auxiliary circuit Screw connection type auxiliary circuit No	
uitable for tube mounting No	on
uitable for angle mounting Yes	
uitable for floor mounting Yes	
Other Other	
uitable for AS interface No	
uitable for M12 connector	
No No	