

## Ba15d continuous light module; yellow

**Part no.** SL4-L-Y  
**171335**  
**EL Number** 4137570  
**(Norway)**

<b>General specifications</b>		
Product name		Eaton Moeller® series SL4 Continuous light module
Part no.		SL4-L-Y
EAN		4015081678723
Product Length/Depth		43 millimetre
Product height		75 millimetre
Product width		43 millimetre
Product weight		0.037 kilogram
Certifications		UL 508 CE UL Category Control No.: NKCR UL CSA-C22.2 No. 14-10 CSA Class No.: NKCR7 IEC/EN 60529 Certified by UL for use in Canada IEC/EN 60947-5-1 UL File No.: E29184 CSA-C22.2 No. 94-91 UL report applies to both US and Canada
Product Tradename		SL4
Product Type		Continuous light module
Product Sub Type		None
Catalog Notes		Without light elements
<b>Features &amp; Functions</b>		
Color		Yellow
Enclosure color		Black
Functions		Continuous light
Light modules		Filament lamp max. 4 W
Number of modules		Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)
<b>General information</b>		
Connection to SmartWire-DT		No
Degree of protection		NEMA 4 IP66
Lifespan, electrical		3,000 h
Light type		Continuous light
Material		Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
Mounting Method		BA15d lamp socket
Mounting position		As required
Overvoltage category		III
Pollution degree		3
Product Category		SL signal towers
Radiation angle		360 °
Rated impulse withstand voltage (Uimp)		4000 V AC
Shock resistance		Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Type		Continuous light module
Voltage type		AC/DC
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-30 °C
Ambient operating temperature - max		60 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78

		Damp heat, cyclic, to IEC 60068-2-30
<b>Electrical rating</b>		
Leakage current		0.003 A
Power consumption		Max. 4 W with the specified voltages
Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) at AC - min		24 V
Rated operational voltage (Ue) at AC - max		250 V
Rated operational voltage (Ue) at DC - min		24 V
Rated operational voltage (Ue) at DC - max		250 V

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss13-27-37-12-20 [AKF038019])		
Function		Continuous light
Repetition frequency settable		No
Colour		Yellow
Outer diameter	mm	43
Operating voltage AC 50 Hz	V	24 - 250
Operating voltage AC 60 Hz	V	24 - 250
Operating voltage DC	V	24 - 250
Voltage type		AC/DC
Power consumption	W	
Lamp type		None
Housing colour		Black
Degree of protection (IP)		IP66
Degree of protection (NEMA)		4