




Acoustic device pulsed tone, 110-230V

Part no. SL-AP110-230
Catalog No. 205344
Alternate Catalog No. SL-AP110-230

Delivery program

Product range			SL signal towers
Single unit/Complete unit			Element
Degree of Protection			IP20
Type of tone			Pulsed tone
Loudness			110 V: 67 dB 230 V: 73 dB
Description			5 Hz with f = 2750 Hz In 60 cm spacing
Rated operational voltage	U _e	V	110 - 230 V AC/DC
Rated operational current	I _e	mA	4 - 8
Colour			Black
			
Connection to SmartWire-DT			no

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Acoustic module for signal tower (EC001261)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, acoustic (ecl@ss10.0.1-27-37-12-37 [AKF055014])			
Function			Pulse tone
Outer diameter		mm	0
Colour			Black
Operating voltage at AC 50 Hz		V	110 - 130
Operating voltage at AC 60 Hz		V	110 - 130
Operating voltage at DC		V	0 - 0
Voltage type			AC
Tone adjustable			No
Degree of protection (IP)			IP20
Degree of protection (NEMA)			
Loudness		dB	

Approvals

Product Standards			IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.			E29184
UL Category Control No.			NKCR
CSA File No.			012528
CSA Class No.			3211-03
North America Certification			UL listed, CSA certified

Dimensions



Additional product information (links)

IL04716024Z (AWA1160-1685) Pillar lamps

IL04716024Z (AWA1160-1685) Pillar lamps

https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716024Z2018_05.pdf